



Digital Barometer 7150 Series

OVERVIEW

AWI's 7150 Series digital barometers are designed to provide accurate pressure measurement over a wide range of environmental temperatures and pressures. The fully compensated digital barometer is ideal for use in demanding automated weather station applications.

These barometers use pressure transducers with silicon peizoresistive absolute pressure sensors. The pressure sensors display low hysteresis, excellent repeatability characteristics, low temperature dependence, and superior long-term stability. The durability of the pressure transducers is outstanding.

All 7150 series barometers can communicate using full-duplex RS-232 or half-duplex RS-485 serial protocols. Both the RS-232 and the RS-485 serial ports are available on the DB9 serial interface, but only one communication protocol is normally used at a time.

The Model 7150 Barometer is Federal Aviation Administration (FAA) certified, meeting or exceeding all current regulatory requirements.

All 7150 Series digital barometers are traceable to the National Institute of Standards and Technology (NIST) in the United States.



MODELS

Three models are offered based on the number of pressure transducers in the digital barometer. Additional pressure transducers allow for operational redundancy, and can be used to flag the digital barometer for maintenance or replacement if the difference in readings between transducers exceeds a predefined amount.

Model Number	Number of Transducers
7150	2
7150-A	3
7150-B	1

* An additional model is available for non-certified system configurations, which will allow for pressure measurements down to 50 hPa. Please ask your AWI sales representative for more information.

SENSORS

SPECIFICATIONS

Parameter	Specification
Pressure Range	14.7-33.0 inHg (500-1117 hPa)
Operating Temperature	-40 to +185°F (-40 to +85°C)
Storage Temperature	-67 to +257°F (-55 to +125°C)
Humidity	noncondensing
Pressure Units	inHg
Resolution	0.001 inHg (0.03 hPa)
Accuracy	±0.004 inHg (±0.1 hPa)
Baud Rate	4800, 9600, 19200, or 57600 bps
Serial Port Parameter Setting	8-N-1 (8 data bits, no parity, 1 stop bit)
Serial Connector	DB9 (female 9-pin D-sub connector)
Supply Voltage	6–40 V DC, reverse polarity protected
Current Consumption	<50 mA (continuous operation mode)
Pressure Fitting	barbed fitting for 1/8" I.D. tubing
Max. Pressure Limit	60 inHg (absolute)
Min. Pressure Limit	0 inHg
Enclosure	powder-coated aluminum

DIMENSIONS & WEIGHTS

Dimensions	5.71" W x 4.72" H x 2.56" D (145 mm x 120 mm x 65 mm)
Weight	23 oz (0.63 kg)
Shipping Weight	34 oz (1 kg)

ORDERING INFORMATION

Digital Barometer Model Number	DCP Kit
7150	11906
7150-A	11906-A
7150-B	11906-B

OPTIONS

Part Number	Description
11906	Dual Digital Barometer Includes: 7150 Dual Barometer, M105037 Quad Plate Pressure Port, and Power/Data Cable
11906-A	Triple Digital Barometer Includes: 7150-A Triple Ba- rometer, M105037 Quad Plate Pressure Port, and Power/Data Cable
11906-B	Single Digital Barometer Includes: 7150-B Single Ba- rometer, M105037 Quad Plate Pressure Port, and Power/Data Cable



Quad Plate Pressure Port
M105037



allweatherinc www.allweatherinc.com
SOLUTIONS PERFORMANCE RESULTS

All Weather Inc.
1165 National Dr.
Sacramento, CA 95834

Phone: 916-928-1000
USA Toll Free: 800-824-5873
Fax: 916-928-1165

Rev. G 11/2015 7150-041