





Features:


- Design Pressure (DP) / Maximum abnormal pressure (MAP): 700 psig, 48 bar
- Continuous operating temperature (COT): -40°F/300°F, -40°C/149°C
- Pressure to open: < 1 psi
- Contact factory or visit website for compatibility with CFC, HCFC, HFC and HFO refrigerants and oils
- UL/cUL Recognized, Conforms to Pressure Equipment Directive 2014/68/EU
- Neoprene seat for positive isolation and pulsation dampening
- Enhanced internal design for maximum flow and minimum pressure drop



Flare to Flare



Solder to Solder



Solder to Solder, Extended Ends

Flare to Flare

Part Number	Size A		B		C		Wt	
	in	mm	in	mm	in	mm	lb	kg
A 15620	1/4	6	2.25	57	13/16 Hex	21 Hex	0.15	0.07
A 15621	3/8	10	2.40	61	13/16 Hex	21 Hex	0.20	0.09
A 15622	1/2	13	3.00	76	1 1/4 Oct	32 Oct	0.43	0.19
A 15623	5/8	17	3.20	81	1 1/4 Oct	32 Oct	0.51	0.23

Solder to Solder

Part Number	Size A		B		C		Wt	
	in	mm	in	mm	in	mm	lb	kg
A 15628 *	1/4	6	1.14	29	13/16 Hex	21 Hex	0.13	0.06
A 15629 *	3/8	10	1.14	29	13/16 Hex	21 Hex	0.13	0.06
A 15630 *	1/2	13	1.44	37	1 1/4 Oct	32 Oct	0.37	0.17
A 15631 *	5/8	17	1.44	37	1 1/4 Oct	32 Oct	0.36	0.16
A 15632 **	1/4	6	4.40	112	13/16 Hex	21 Hex	0.16	0.07
A 15633 **	3/8	10	4.70	119	13/16 Hex	21 Hex	0.18	0.08
A 15634 **	1/2	13	4.90	124	1 1/4 Oct	32 Oct	0.43	0.20
A 15635 **	5/8	17	5.20	132	1 1/4 Oct	32 Oct	0.48	0.22

* Shipped loosely assembled
** Extended Ends