



ELECTRICAL SPECIFICATIONS

STYLE: ISOLATED SEC, EPOXY ENCAPSULATED IGNITION TRANSFORMER
 PRIMARY: 120V. 60HZ.
 PRIMARY LEAD WIRES TO BE 48" OUT OF ENCLOSURE
 SECONDARY: 6000V. AT 22 MA. ISOLATED
 INSULATION SYSTEM: 180° C MINIMUM
 TEMPERATURE RAISE: 55° C MAXIMUM
 RATING: 150 VA.
 MAXIMUM SECONDARY CURRENT: 25 MA. (SHORT CIRCUIT CURRENT)
 MAXIMUM AMBIENT TEMPERATURE: 180° F
 U.L.LISTED: FILE #E12339
 CSA. CERTIFIED FILE #LR 560

REV: C ADDED PRI NOTE & CSA PER CUST JL 7/30/02	TITLE: OUTLINE FOR 6000 VOLTS 1PH. 60HZ.		
REV: B BUSHINGS WERE LEAD WIRES PER CUST JL 6/17/02	IGNITION TRANSFORMER		
REV: A ADD UL FILE DS 6/3/02			
DONGAN ELECTRIC MFG. CO. PIONEER TRANSFORMER CO.	TOLERANCES DECIMAL DIMENSIONS ±.030 FRACTIONAL DIMENSIONS ±1/32	MADE BY JL	DATE 5/31/02
	SCALE: 3D	PART NUMBER A06-SA6X-ISO	CHECKED & APPROVED DRAWING NUMBER 10-832