

The Innovative Solution with High Performance,
an Abundant Selection and Amazing Expandability.



Automation for a Changing World

Delta Programmable Logic Controller DVP Series



reddot design award
winner 2010

www.deltaww.com

 **DELTA**
Smarter. Greener. Together.


The Perfect Small PLC Revolution!


After launching our first DVP series PLCs for industrial automation applications, Delta has been devoted to delivering more innovative products that satisfy customers' needs and meet the requirements of a wide variety of applications.

Delta PLCs offer a broad range of controllers and modules which all feature high performance, multiple functions and efficient program editing tools. In addition to the user-friendly programming software and faster execution speed, we also provide complete industry-focused solutions, motion control solutions, and industrial fieldbus solutions with Delta's new PLC series.

We integrate our PLCs with industrial automation products to deliver total solutions for various field applications.

As your most reliable partner, Delta is dedicated to creating value for our customers.





Contents

	Page
Standard PLC DVP-E Series	5
Slim PLC DVP-S Series	8
General Motion Controller DVP-PM Series	11
Multi-axis Motion Controller DVP-MC Series	13
DVP Series Extension Modules	21
Electrical Specifications	26
Dimensions	27
PLC Editing Software ISPSoft	31
Touch / Text Panel HMI with Built-in PLC TP Series	33
DVP Series Model Name Instruction	37
DVP Series Function Overview	38
Ordering Information	39



NEW

Built-in Ethernet for Advanced Applications



Standard PLC **DVP-ES2-E**

- ▶ Built-in 20 / 32 / 40 / 60 I/O points
- ▶ Built-in Ethernet port that supports MODBUS TCP and EtherNet/IP (slave)

Increased Built-in I/O Points to Enhance Competitiveness for Solutions

PLCs

DVP-28SS2 **DVP-28SA2** **DVP-26SE**

- ▶ 16DI + 12DO (DVP-28SS2, DVP-28SA2)
- ▶ 14DI + 12DO (DVP-26SE)
- ▶ Compatible with DVP-S Series extension modules (right-side)



Complete Interface Design and 24-axis Motion Control



CANopen Motion Controller **DVP-15MC**

EtherCAT Motion Controller **DVP-50MC**

- ▶ 1GHz CPU
- ▶ Program capacity + data capacity = 20MB + 20MB
- ▶ Up to 24 real axes control

Built-in Interface

16DI
8DO

RS-232

RS485

Ethernet
15MC: x2
50MC: x1

Memory
card:SD

CANopen
DS301

Motion
15MC: CANopen
DS402
50MC: EtherCAT

Incremental
encoder
interface*2

SSI absolute
encoder
interface

Motion Function

Multi-axis Gear
/ Cam

Linear / Arc
/ Helical
interpolation

Jerk

G-Code

Buffer
Mode



reddot design award
winner 2010

Basic PLC DVP-EC3

Applicable for sequence control and simple RS-485/MODBUS communication

- ▶ Built-in I/O: 10/14/16/20/24/30/32/40/48/60
 - ▶ Program capacity: 4 k steps
 - ▶ COM port: Built-in RS-232 & RS-485 ports (10/14-point models do not support RS-485), compatible with MODBUS ASCII/RTU protocol
 - ▶ Supports 2 points (Y0, Y1) of independent high-speed (max. 10kHz) pulse output
- (Hardware version V8.00 and above support this function)

Built-in High-Speed Counters					
1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
2/2	20kHz/10kHz	1	20kHz	1	4kHz

Standard PLC / Analog I/O PLC DVP-ES2/EX2

Standard PLCs with integrated communication and highly efficient processing ability for your control systems

- ▶ 32-bit CPU for high-speed processing
- ▶ Standard PLC DVP-ES2 Series: 16/20/24/32/40/60/80 I/O points for a variety of applications
- ▶ Analog I/O PLC DVP-EX2:
 - Built-in 12-bit 4 analog inputs / 2 analog output; and 14-bit analog I/O extension module
 - Built-in PID auto tuning function for a complete analog control solution
- ▶ Built-in 1 RS-232 and 2 RS-485 ports
- ▶ Program capacity: 16k steps
- ▶ Data register: 10k words
- ▶ Max. execution speed of basic instructions: 0.35 µs
- ▶ RTC function and file register (5k words) (hardware version 2.0 and above)
- ▶ Highly efficient processing ability: 1k steps of programs can be completed within 1ms
- ▶ Max. 100 kHz pulse control; specific motion control instructions (mark/masking and instant frequency changing) available for multi-axis applications
- ▶ Up to 4 levels of password protection secures your source programs and intellectual property

Built-in High-Speed Counters					
1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
2/6	100kHz/10kHz	2	100kHz	1/3	15kHz/5kHz



Standard PLC with built-in CANopen interface

DVP32ES200RC/TC


Boosts productivity with high execution speed and built-in CANopen interface, and specializes in noise-immunity and easy wiring

- ▶ Built-in 1Mbps CANopen interface; COM3 supports standard CANopen DS301 protocol
- ▶ Versatile communication types: PDO, SDO, synchronous (SYNC), Emergency, NMT and many more
- ▶ 1Mbps high-speed transmission for large data:
 - Max. PDO transmission: up to 390 bytes
 - Max. PDO receiving: up to 390 bytes
- ▶ Ability to connect with 16 slaves via CANopen
- ▶ Built-in 1 RS-232 and 1 RS-485 ports

Fast processing speed



High-speed industrial network: CANopen



Standard PLC with built-in Ethernet interface

DVP-ES2-E

Higher communication speed and easier external connection with built-in Ethernet

- ▶ Built-in I/O: 20/32/40/60
- ▶ Communication speed: 100M
- ▶ Supports MODBUS and EtherNet/IP (slave)
- ▶ Built-in 1 RS-232 and 2 RS-485 ports

Temperature / Analog I/O PLC

DVP30EX200R/T

Integrated controller for temperature control and analog input

- ▶ Built-in 16-bit 3 analog inputs / 12-bit 1 analog output
- ▶ Built-in PID auto tuning function to offer a complete analog control solution
- ▶ 3 analog inputs for Pt / Ni temperature input, precision of 0.1 degree can be readily achieved

Built-in Ethernet			
MODBUS		EtherNet/IP	
Number of Connections	Server: 16 Client: 8	Number of Connections	TCP: 4 CIP: 8
Max. Data Exchange (each connection)	100 words	Max. Data Exchange (each connection)	250 words
		RPI	5~1,000 ms
		PPS	1,000 PPI

Built-in Analog I/O in DVP-EX2 Model			
Analog Input		Analog Output	
Channels	3	Channels	1
Resolution	16-bit	Resolution	12-bit
Spec.	-20~20 mA or -10~10 V	Spec.	0~20 mA or -10~10 V

Built-in Temperature Control Function		
Sensor	Pt100/Pt1000	Ni100/Ni1000
Temperature Range	-200°C~800°C	-100°C~180°C
Value Range	-2,000~8,000	-1,000~1,800




High Performance PLC


DVP-EH3

High-end model of Delta's DVP-E Series PLC with large program capacity and data registers for demanding and complex applications


Program capacity



Data register



Execution speed



Excellent Motion Control

- High-speed pulse output: 4 axes of 200 kHz pulse output (DVP32/40/48/64/80EH00T3)
- Supports max. 4 hardware 200 kHz high-speed counters
- Various motion control instructions to achieve high-speed and high-precision positioning control for labeling machines, packaging machines, printing machines and more applications
- Linear / arc interpolation motion control function
- Provides up to 16 external interrupt pointers

Complete Program Protection

- Auto backup function prevents program and data loss even when the battery runs out
- Secondary backup function saves an extra copy of programs and data to enhance program safety
- Up to 4 levels of password protection protects your source programs and intellectual property

Outstanding Operation Performance

- 32-bit CPU + ASIC dual processors support floating point operations
- Max. execution speed of basic instructions: 0.24 μ s

Flexible Function Extension Modules & Cards

- Multiple selections of extension modules and function cards: analog I/O, temperature measurement, additional single-axis motion control, high-speed counting
- 3rd serial communication port and Ethernet communication card are available

PLC Link

- PLC Link allows users to link up a max. of 32 units to the network without extra communication extension modules

Built-in 4 Hardware High-Speed Counters							
Standard		Hardware high-speed counter					
1-phase 1 input		1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
8	10kHz	4	200 kHz	4	200 kHz	4	200 kHz


The specifications of high-speed input and output on this page are applicable only for DVP40EH00R3 / DVP40EH00T3.

Refer to the I/O specifications table on page 20 for more information on other models.



High Performance Slim PLC DVP-SV2

High-end model of the DVP-S Series with larger program capacities and data registers for more demanding and complex applications



Excellent Motion Control

- High-speed pulse output: 4 axes of 200 kHz pulse output
- Supports 4 hardware 200 kHz high speed counters
- Various motion control instructions to achieve high-speed and high-precision positioning control for labeling machines, packaging machines, printing machines and more applications
- Linear / arc interpolation motion control function
- Provides up to 16 external interrupt pointers

Complete Program Protection

- Auto backup function prevents program and data loss even when the battery runs out
- Secondary backup function saves an extra copy of programs and data to enhance program safety
- Up to 4 levels of password protection protects your source programs and intellectual property

Supports DVP-S Series modules (left-side and right-side); additional new Ethernet communication command (ETHRW)

Outstanding Operation Performance

- 32-bit CPU + ASIC dual processors support floating point operations
- Max. execution speed of basic instructions: 0.24 μ s

The DVP-24SV2 model has a built-in 2AI (12-bit) with Y10/Y12 of 10kHz output.

Built-in 4 Hardware High-Speed Counters

Standard		Hardware high-speed counter					
1-phase 1 input		1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
8	10kHz	4	200 kHz	4	200 kHz	4	200 kHz

The X11 / X15 have been upgraded to 200kHz since 2016 October



Standard Slim PLC DVP-SS2

Economic and compact model

- ▶ 32-bit CPU for high-speed processing
- ▶ Max. I/O: 480 points
- ▶ Program capacity: 8k steps
- ▶ Data register: 5k words
- ▶ Max. execution speed of basic instructions: 0.35 µs
- ▶ Built-in RS-232 and RS-485 ports (Master/Slave)
- ▶ Supports standard MODBUS ASCII/RTU protocol and PLC Link function

Motion Control Functions

- ▶ 4 points of 10 kHz pulse output
- ▶ 8 points of high-speed counters: 20 kHz/4 points, 10 kHz/4 points

Advanced Slim PLC DVP-SA2

Advanced model supporting 2-axis interpolation

- ▶ 32-bit CPU for high-speed processing
- ▶ Program capacity: 16 k steps
- ▶ Data register: 10 k words
- ▶ Max. execution speed of basic instructions: 0.35 µs
- ▶ Built-in 1 RS-232 and 2 RS-485 ports (Master/Slave)
 - ※ Note: RS-485 will be reduced to 1 port in DVP28SA2
- ▶ Supports standard MODBUS ASCII/RTU protocol and PLC Link function
- ▶ No battery required; RTC function operates for 15 days after power off
- ▶ Supports DVP-S Series modules (left-side and right-side)
 - ※ Note: DVP28SA2 only supports right-side modules

Motion Control Functions

- ▶ 4 points of high-speed pulse output: 100 kHz/2 points, 10 kHz/2 points
- ▶ 8 points of high-speed pulse input: 100 kHz/2 points, 10 kHz/6 points, 1 set of A/B phase 50 kHz
- ▶ Supports 2-axis linear and arc interpolation

Built-in High-Speed Counters					
1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
4/4	20 kHz/ 10 kHz	2	20 kHz	2/2	10 kHz/ 5 kHz

Built-in High-Speed Counters					
1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
2/6	100 kHz/10 kHz	2	100 kHz	1/3	50 kHz/5 kHz



Analog I/O Slim PLC DVP-SX2

Analog model with highly efficient PID control function

- ▶ 32-bit CPU for high-speed processing
- ▶ Program capacity: 16 k steps
- ▶ Data register: 10 k words
- ▶ Max. execution speed of basic instructions: 0.35 µs
- ▶ Built-in 4 analog inputs / 2 analog outputs
- ▶ Built-in mini USB, RS-232 and RS-485 ports (Master/Slave)
- ▶ Supports standard MODBUS ASCII/RTU protocol and PLC Link function
- ▶ PID Auto Tuning function for highly efficient PID control
- ▶ No battery required; RTC function operates for at least one week after power off (hardware version 2.0 and above)
- ▶ Supports DVP-S Series modules (left-side and right-side)

Motion Control Functions

- ▶ 4 points of high-speed pulse output: 100 kHz / 2 points, 10 kHz / 2 points
- ▶ 8 points of high-speed pulse input: 100 kHz / 2 points, 10 kHz / 6 points
- ▶ Supports 2-axis linear and arc interpolation

Built-in Analog I/O			
Analog Input		Analog Output	
Channels	4	Channels	2
Resolution	12-bit	Resolution	12-bit
Spec.	-20~20 mA or -10~10 V or 4~20 mA	Spec.	0~20 mA or -10V~10V or 4~20 mA

Network Type Advanced Slim PLC DVP-SE

Complete network communication functions for advanced industrial applications

- ▶ 32-bit CPU for high-speed processing
- ▶ Program capacity: 16 k steps
- ▶ Data register: 12 k words
- ▶ Max. execution speed of basic instructions: 0.64 µs
- ▶ Built-in Ethernet
 - DVP12SE : MODBUS & Ethernet/IP (Explicit message)
 - DVP26SE : MODBUS & Ethernet/IP (Adapter mode, explicit message)
- ▶ Built-in mini USB port, RS-485 port*2 and Ethernet port that supports MODBUS TCP and EtherNet/IP Slave (adapter)
 - ※ Note: RS-485 will be reduced to 1 port in DVP26SE
- ▶ IP Filter functions as firewall for first line protection against malware and network threats
- ▶ Supports DVP-S Series modules (left-side and right-side)
 - ※ Note: DVP26SE only supports right-side modules
- ▶ No battery required; RTC function operates for 15 days after power off

Motion Control Functions

- ▶ 4 points of high-speed pulse output: 100 kHz / 2 points, 10 kHz / 2 points
- ▶ 8 points of high-speed pulse input: 100 kHz / 2 points, 10 kHz / 6 points, 1 set of A / B phase 50 kHz
- ▶ Supports 2-axis linear and arc interpolation

Built-in High-Speed Counters					
1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
2/6	100 kHz / 10 kHz	2	100 kHz	1/3	50 kHz / 5 kHz

General Motion Controller

DVP-PM



Standard Motion Controller

DVP10PM00M

Standard motion controller for general applications

- ▶ Built-in 24 I/O points. Max. 256 I/O points
- ▶ Program capacity: 64 k steps
- ▶ Data register: 10 k words
- ▶ Execution speed LD: 0.13 µs, MOV: 2.1 µs
- ▶ Built-in RS-232 and RS-485 ports
- ▶ 2 / 3 / 4 / 5 / 6 axes linear interpolation motion control
- ▶ Highly accurate PWM 200 kHz output, resolution 0.3%
- ▶ 8 groups of high-speed captures (mark correction, frequency measurement), comparative output, Mark / Mask function (for bag making)
- ▶ Supports standard MODBUS ASCII / RTU protocol

Motion Control Functions

- ▶ High-speed pulse output: built-in 6 sets of A/B phase pulse outputs
- ▶ 2 sets of 200 kHz output, 4 sets of 1 MHz output
- ▶ 6 sets of high-speed counters and hardware digital filter for counting
- ▶ Supports MPG inputs
- ▶ Single-axis motion control function (supports MPG, single-speed and two-speed positioning)
- ▶ Electronic gear function

Advanced Motion Controller

DVP20PM00D / M / DT

Excellent as motion controllers or extension modules and supports advanced motion control functions

- ▶ Built-in 16 I/O points. Max. 512 I/O points
- ▶ Program capacity: 64 k steps
- ▶ Data register: 10 k words
- ▶ Compatible with G-code / M-Code
- ▶ 3-axis linear/arc/helical interpolation
- ▶ Supports electronic cam (2,048 points) function for flying shear and rotary cut applications
- ▶ All models can be applied as motion controllers or extension modules
- ▶ Built-in RS-232 and RS-485 ports, and supports standard MODBUS ASCII/RTU protocol

Motion Control Functions

- ▶ Built-in A/B phase differential signal outputs: 2 sets (DVP20PM00D)/3 sets (DVP20PM00M)
Max. differential output frequency: 500 kHz
- ▶ Supports MPG inputs
- ▶ Single-axis motion control function (supports MPG, single-speed and two-speed positioning)
- ▶ Electronic gear function

Function Cards for DVP-PM

Model Name	Specifications	Features
DVP-FPMC	Ethernet/CANopen communication card	<ol style="list-style-type: none">1. Complies with CANopen CiA301 V4.0.2 protocol.2. Provides high-speed program upload/download via Ethernet.

* DVP-PM also supports DVP-EH series function cards: DVP-F2AD, DVP-F2DA, DVP-F232S and DVP-F485S

General Motion Controller DVP-PM Series: Pulse-train communication



Programming Software for DVP-PM Series: PMSoft

The programming software for G-Code editing, motion path simulation, positioning route planning and electronic cam setup

System Information

- Program
 - Program
 - Main FBs
 - O100_(10)
 - C_Ox
 - P
 - I
 - Instruction
 - XYChart
 - MonitorTable_Xaxis
 - MonitorTable_Yaxis
 - MonitorTable_Zaxis
 - Symbols Allocation
 - Global Symbols
- Function Blocks
 - FPMC_Scan
 - FPMC_Servo_On/OFF
 - FPMC_WPparameter
 - FPMC_ReadParameter
 - FPMC_PP_Mode
 - FPMC_Home_mode
 - FPMC_Drive_Status
- + Libraries
- + Device Comments
- + DVP-FPMC
- CAM Chart
 - 0
 - 1
 - 2
- + PEP Setting

Variable Declaration

Separate from the program. The corresponding physical I/O point of the variable is defined only after the program is compiled. Users do not need to modify the program.

Class	Identifier	Address	Type	Init	Comment
VAR	Axi_Step		FPMC_Scan		FPMC步进轴启停
VAR	Axi_Enable		FPMC_Servo_OnOff		FPMC伺服启停
VAR	Axi_WP		FPMC_WPparameter		FPMC限位参数
VAR	Axi_PP		FPMC_HeadStart		FPMC启动脉冲进给

Function Block

- A completed project can be divided into many function blocks.
- Every function block can be used repeatedly, and the import / export function makes the programming more convenient.

Comprehensive Monitoring

The "program monitoring" and "device monitoring" allow users to keep track of program operation.

Motion Network Function Block

PLCopen Function Block allows users to easily use motion control functions

Electronic Cam

Electronic cam editing

12

 **DELTA**

Multi-axis Motion Controller


DVP-MC

16-axis Motion Controller


DVP10MC11T

Perfect controller to offer highly stable multi-axis motion control solutions through CANopen communication

- ▶ Built-in 12 I/O points
(8 sets of high-speed inputs,
4 sets of high-speed outputs)
- ▶ Up to 16 axes synchronous control through
CANopen communication
- ▶ Synchronization time: 4 axes in 2ms / 8 axes in
4ms
- ▶ Built-in motion control instructions of electronic
cam, flying shear, rotary cut for easy operation
- ▶ High precision control with interpolation function



System Control Architecture



CANopen Accessories

Model Name	Specifications	Features
	CANopen sub-line	RJ45 connector for both ends
	CANopen main-line / sub-line	AWG18/AWG24 CANopen cables for long distance communication via CANopen
	Distribution box	Built-in terminal resistor 120Ω
	Terminal resistor	Terminal resistor 120Ω

6 and 24-axis Motion Controller

DVP15MC / DVP50MC series new

The DVP15MC/DVP50MC Series is a multi-axis motion controller designed for the CANopen / EtherCAT network architecture. It supports CANopen/EtherCAT with built-in motion control instructions (BufferMode and Jerk) for flexible configuration and fast project development. DVP15MC/DVP50MC controls up to 24 real axes via Motion port. It also supports single axis motion control instructions such as speed, position, torque, homing, position setup and multi-axis motion control instructions such as electronic gear, electronic cam (E-Cam), rotatory cut and G-code.

DVP15MC/DVP50MC features multiple built-in communication interfaces, and can be easily connected to other equipment without additional communication modules. It also provides high-speed and reliable motion control via CANopen/EtherCAT for printing, packaging, wire cutting, robots and other automation control industries.

Motion Control

- Up to 24 real axes control
(virtual axis no.: 1 ~ 32, can't be repetitive with real axis no.)
- Built-in motion control instructions and easy to use
- Supports encoder axis and virtual axis
- Single axis motion control instructions: speed, torque, homing, and position setup
- Application instructions: electronic gear, E-Cam, and rotary cut
- G-code: 8 axes linear/arc/helical interpolation
- Coordinates motion control instructions

Performance

- 1 GHZ high-speed floating point operation
- High-precision computing: supports LREAL
(Double-precision floating-point format)
- Synchronization time:
 - DVP15MC: 4 axes in 2ms, 8 axes in 4ms
 - DVP50MC: 32 axes in 1ms
- Program capacity: 20 MB
- Data capacity: 20 MB



External Interfaces


- 1 CANopen port as host or slave station
- 1 Motion port (DVP15MC: CANopen, DVP50MC: EtherCAT)
- 16 high-speed inputs/8 high-speed outputs
- 2 incremental encoder interfaces
- 1 SSI absolute encoder interface
- Ethernet port: DVP15MC x2, DVP50MC x1
- 1 SD card slot
- 1 RS-232 port and 1 RS-485 port
- Extension:
 - Left-side: supports up to 8 DVP-S Series modules
(master/slave/load cell modules)
 - Right-side: compatible with DVP-S Series modules
(240 I/O, 8 special modules)

Motion Network and Wiring

- DVP15MC
 - Motion network: CANopen
 - Communication speed: Max. 1Mbps
 - Distance: Max. 100m (at 500 kbps)
- DVP50MC
 - Motion network: EtherCAT
 - Communication speed: Max. 100Mbps
 - Distance: Max. 50m (Node-to-node)
- Simple wiring, plug-and-play

DVP15MC / DVP50MC Interface

Multiple built-in communication interfaces allow easy connection to other equipment without additional communication modules.




Simple Wiring, Plug-and-Play Motion Control Network


The DVP15MC/DVP50MC features stable CANopen / EtherCAT communication, simple wiring, plug-and-play functions, and communicates with servo drives (axes) via CANopen/EtherCAT network. Delta provides communication cable, terminal resistor and distribution box.

*Please refer to "Accessories" for detail information.

DVP15MC:



DVP50MC:



Compatible with Servo Drives via Motion Port

- Delta's AC Motor Drives ASDA-A2-XXXX*-M models support CANopen communication, and they are the only models that can be connected to a DVP15MC CANopen (Motion) port and DVP10MC11T for motion control networks.
- Delta's AC Motor Drives ASDA-A2-XXXX*-E models support EtherCAT communication, and they are the only models that can be connected to a DVP50MC EtherCAT (Motion) port for motion control networks.


The standard CANopen port of DVP15MC/DVP50MC can be connected to all equipment that supports CANopen networks. The ASDA-A2 Series models provide high positioning accuracy and low-speed operation stability when matched with ECMA Series servo motors with high-precision encoder (20-bit resolution and 1,280,000 pulse/rev).


* XXXX represents output power and input voltage.



System Structure


DVP15MC/DVP50MC provides multiple industrial networks. As in the structure shown below, DVP15MC /DVP50MC can be connected to a variety of industrial automation equipment via Ethernet (upper layer), EtherCAT, CANopen, DeviceNet, PROFIBUS DP (middle layer) and RS-485 (lower layer, support Modbus).






Motion Control


Supports BufferMode and Jerk motion instructions:



Supports Jerk motion instruction: modify the Jerk value to make the velocity curve smoother



Supports BufferMode motion instruction: enables smooth transition between 2 instructions



CANopen Configuration Software: CANopen Builder

- Features network arrangement, motion control programming, G-code editor / graph preview and E-Cam curve planning
- Supports international standard function blocks for motion control, enhancing program editing efficiency

The screenshot shows the CANopen Builder software interface with four main sections highlighted by arrows:

- Network Arrangement**: Shows a tree view of network equipment and a diagram of nodes (N0, N1, N2) connected via CAN.
- Motion Control**: Shows a list of international standard function blocks for motion control.
- G-code Editor and Preview**: Shows a G-code editor window with a preview of a helical path and a graph preview window.
- E-Cam Curve Planning**: Shows a graph of E-Cam curves with multiple profiles plotted.

Professional Motion Control Applications

Designed as the most outstanding and economical motion controller, the DVP-PM Series provides flying shear, rotary cut, electronic cam and many advanced functions to achieve highly precise motion control

Robot Arm

Electronic Cam (E-Cam) function enables the robot arm to perform multi-axis control. After the required positions are memorized in the PLC, users can enable the electronic cam function to create the E-Cam profile and conduct trajectory tracking and multi-axes motion control required in robot arm applications.



High-Speed Cutting Machine

Average PLC cutting motion is limited by operation speed, poor synchronization, large amounts of calculations and long CPU processing time, resulting in a disproportionate cutting result and affecting the quality of end products. The basic demands, however, can be fulfilled under low speed while rough surface and low quality appear under high speed. The electronic cam function offered by DVP-PM and DVP-MC is able to generate dynamic cam curves for rotary cutting to ensure precise cutting results.



Digital Board Cutting Machine

The DVP-PM Series' built-in flying shear function is able to complete synchronous conveyance and cutting speed, and ensures precise cutting results on conveyor belts.



CNC Lathe

The DVP-PM Series controls multi-axis motion. Two axes complete the motion by linear or arc interpolation, and the other two work independently, controlling the independent or synchronous ascending/descending of the vertical axis on two sides.



High Performance PLC DVP-EH Series and Extension Modules

Small PLC with Highest Operation Efficiency

DVP-EH3

- ▶ Max. 512 I/O points
- ▶ 200 kHz high-speed pulse output
- ▶ High-speed extension modules
- ▶ Linear/Arc interpolation
- ▶ L type, supports extension modules (left-side)



Function Cards

■ RS-232/RS-422/RS-485 Communication (COM3 Port, DVP-EH3 series PLC only)

DVP-F232



DVP-F422



DVP-F485



■ Ethernet Communication

DVP-FEN01 (DVP-EH3 only)



■ Analog I/O

DVP-F2AD

DVP-F2DA



Accessories

■ Data Backup Card

DVP-512FM (DVP-EH3 only)



DVPPCC01
(for general applications)



■ Data Transmission Cable

UC-MS030-01A



Model Name	Specifications
DVP16EH00R3	2 counters of 200 kHz input
DVP16EH00T3	2 counters of 200 kHz input, 2 axes of 200 kHz output
DVP20EH00R3	2 counters of 200 kHz input, 1 counter of 20 kHz input
DVP20EH00T3	2 counters of 200 kHz input, 2 axes of 200 kHz output
DVP32EH00R3	4 counters of 200 kHz input
DVP32EH00T3 ²	4 counters of 200 kHz input, 4 axes of 200 kHz output
DVP32EH00M3	4 counters of 200 kHz input (Differential: 2 sets), 2 axes of 200 kHz output (Differential: 2 axes)
DVP32EH00MT New	4 counters of 200 kHz input (Differential: 2 sets), 2 axes of 200 kHz output (Differential: 2 axes)
DVP32EH00R3-L ¹	4 counters of 200 kHz input
DVP32EH00T3-L ^{1,2}	4 counters of 200 kHz input, 4 axes of 200 kHz output
DVP40EH00R3	4 counters of 200 kHz input
DVP40EH00T3	4 counters of 200 kHz input, 4 axes of 200 kHz output
DVP48EH00R3	4 counters of 200 kHz input
DVP48EH00T3	4 counters of 200 kHz input, 4 axes of 200 kHz output
DVP64EH00R3	4 counters of 200 kHz input
DVP64EH00T3	4 counters of 200 kHz input, 4 axes of 200 kHz output
DVP80EH00R3	4 counters of 200 kHz input
DVP80EH00T3	4 counters of 200 kHz input, 4 axes of 200 kHz output

—AC— AC power supply Inputs Outputs Relay output Transistor output Differential output

*1 Supports high-speed extension (left-side).

*2 DVP32EH Series produced after 2014 support 4 axes of 200 kHz output

Digital I/O Modules

Input Point Extension

- DVP08HM11N
- DVP16HM11N
- DVP32HM11N



Output Point Extension

- DVP08HN11R/T
- DVP32HN00R/T



Input/Output Point Extension

- DVP08HP11R/T
- DVP16HP11R/T
- DVP32HP00R/T
- DVP48HP00R/T



Analog I/O Modules

Analog Function Extension

Analog Input

- DVP04AD-H2
V: 14-bit
I: 13-bit
- DVP04AD-H3
V: 16-bit
I: 16-bit



Analog Output

- DVP04DA-H2
V: 12-bit
I: 12-bit
- DVP04DA-H3
V: 16-bit
I: 16-bit



Analog Input/Output

- DVP06XA-H2
Input 4CH/Output 2CH
V: 12-bit/V : 12-bit
I: 11-bit/I : 12-bit
- DVP06XA-H3
V: 16-bit
I: 16-bit



Temperature Measurement

Sensor: Pt100

- DVP04PT-H2



Sensor:

- DVP04TC-H2
J, K, R, S, E, N, T
thermocouple
0 ~ 150mV
- DVP08TC-H2
J, K, R, S, E, N, T
thermocouple
±150mV



DVP32EH00R3-L & DVP32EH00T3-L: compatible with DVP-SV Series' high-speed extension modules (left-side)



Motion Control

Single-Axis Positioning

- DVP01PU-H2



High-Speed Counter

- DVP01HC-H2

Standard PLC DVP-ES2 / EX2 Series and Extension Modules

The Most Profitable Solution for Sequential Control

DVP-ES2 / EX2

- ▶ 100 kHz pulse output
- ▶ Analog input/output

Model Name	Specifications
DVP16ES200R	-E- C 8 ↑ 8 R→
DVP16ES200T	-E- C 8 ↑ 8 T→
DVP20ES200RE <small>New</small>	-E- C 12 ↑ 8 R→ 2E
DVP20ES200TE <small>New</small>	-E- C 12 ↑ 8 T→ 2E
DVP24ES200R	-E- C 16 ↑ 8 R→
DVP24ES200T	-E- C 16 ↑ 8 T→
DVP32ES200R	-E- C 16 ↑ 16 R→
DVP32ES200T	-E- C 16 ↑ 16 T→
DVP32ES211T	-DC- C 16 ↑ 16 T→
DVP32ES200RC	-E- C 16 ↑ 16 R→ C
DVP32ES200TC	-E- C 16 ↑ 16 T→ C
DVP32ES200RE <small>New</small>	-E- C 16 ↑ 16 R→ 2E
DVP32ES200TE <small>New</small>	-E- C 16 ↑ 16 T→ 2E
DVP40ES200R	-E- C 24 ↑ 16 R→
DVP40ES200T	-E- C 24 ↑ 16 T→
DVP40ES200RE <small>New</small>	-E- C 24 ↑ 16 R→ 2E
DVP40ES200TE <small>New</small>	-E- C 24 ↑ 16 T→ 2E
DVP60ES200R	-E- C 36 ↑ 24 R→
DVP60ES200T	-E- C 36 ↑ 24 T→
DVP60ES200RE <small>New</small>	-E- C 36 ↑ 24 R→ 2E
DVP60ES200TE <small>New</small>	-E- C 36 ↑ 24 T→ 2E
DVP80ES200R <small>New</small>	-E- C 40 ↑ 40 R→
DVP80ES200T <small>New</small>	-E- C 40 ↑ 40 T→
-E- AC power supply	C Inputs
-DC- DC power supply	U Outputs
	R→ Transistor output
	E Ethernet
	C CANopen

DVP-EX2

Model Name	Specifications
DVP20EX200R	-E- C 8 ↑ 6 R→ 4AI/2AO
DVP20EX200T	-E- C 8 ↑ 6 T→ 4AI/2AO
DVP30EX200R	-E- C 16 ↑ 10 R→ 3AI/1AO
DVP30EX200T	-E- C 16 ↑ 10 T→ 3AI/1AO
-E- AC power supply	C Inputs
-DC- DC power supply	U Outputs
	R→ Transistor output
	R→ Relay output



reddot design award
winner 2010

Digital I/O Modules

Input Point Extension

DVP08XM211N
DVP16XM211N

Output Point Extension

DVP08XN211R/T
DVP16XN211R/T
DVP24XN200R/T

Input/Output Point Extension

DVP08XP211R/T
DVP16XP211R/T
DVP24XP200R/T
DVP32XP200R/T



Analog I/O Modules

Input Point Extension

DVP04AD-E2

Output Point Extension

DVP04DA-E2
DVP02DA-E2

Input/Output Point Extension

DVP06XA-E2



Temperature Measurement Modules

DVP04PT-E2

DVP04TC-E2

Resolver Modules

DVP10RC-E2¹



DVP-ES2 Series Extension Cable Modules

DVPAEXT01-E2



¹*1. Contact your sales representative for the official launch date of the DVP10RC-E2 module.

Slim PLC DVP-S Series

Compact, Flexible Extension

DVP-SS2

Standard Slim PLC



Model Name	Specifications			
DVP28SS211R <small>New</small>	—DC—	16 ↗	12 ↑	↗ R
DVP28SS211T <small>New</small>	—DC—	16 ↗	12 ↑	↗ T
DVP14SS211R	—DC—	8 ↗	6 ↑	↗ R
DVP14SS211T	—DC—	8 ↗	6 ↑	↗ T
DVP12SS211S	—DC—	8 ↗	4 ↑	↗ S

—DC— DC power supply ↗ Inputs ↑ Outputs
 ↗ T → Transistor output (NPN) ↗ R → Relay output
 ↗ S → Transistor output (PNP)

DVP-SA2

Advanced Slim PLC



Model Name	Specifications			
DVP28SA211R ¹ <small>New</small>	—DC—	16 ↗	12 ↑	↗ R
DVP28SA211T ¹ <small>New</small>	—DC—	16 ↗	12 ↑	↗ T
DVP12SA211R	—DC—	8 ↗	4 ↑	↗ R
DVP12SA211T	—DC—	8 ↗	4 ↑	↗ T

¹ The DVP28SA2 models do not support left-side modules.

—DC— DC power supply ↗ Inputs ↑ Outputs
 ↗ T → Transistor output (NPN) ↗ R → Relay output

DVP-SE

Network Type Advanced Slim PLC



Model Name	Specifications			
DVP26SE11R <small>New</small>	—DC—	14 ↗	12 ↑	↗ R
DVP26SE11T <small>New</small>	—DC—	14 ↗	12 ↑	↗ T
DVP12SE11R	—DC—	8 ↗	4 ↑	↗ R
DVP12SE11T	—DC—	8 ↗	4 ↑	↗ T

—DC— DC power supply ↗ Inputs ↑ Outputs
 ↗ T → Transistor output (NPN) ↗ R → Relay output



DVP-SX2

Analog I/O Slim PLC

Model Name	Specifications			
DVP20SX211R	—DC—	8 ↗	6 ↑	↗ R → 4AI/2AO
DVP20SX211T	—DC—	8 ↗	6 ↑	↗ T → 4AI/2AO
DVP20SX211S	—DC—	8 ↗	6 ↑	↗ S → 4AI/2AO

—DC— DC power supply ↗ Inputs ↑ Outputs
 ↗ T → Transistor output (NPN) ↗ R → Relay output
 ↗ S → Transistor output (PNP)




DVP-SV2

High Performance Slim PLC

Model Name	Specifications			
DVP28SV11R2	—DC—	16 ↗	12 ↑	↗ R
DVP28SV11T2	—DC—	16 ↗	12 ↑	↗ T
DVP28SV11S2	—DC—	16 ↗	12 ↑	↗ S
DVP24SV11T2	—DC—	16 ↗	12 ↑	↗ T → 2AI

—DC— DC power supply ↗ Inputs ↑ Outputs
 ↗ T → Transistor output (NPN) ↗ R → Relay output
 ↗ S → Transistor output (PNP)



Slim PLC DVP-S Series

Extension Modules

High-speed Extension Modules (left-side) ^{*1}	General Extension Modules (right-side) ^{*2}		
Network Modules	I/O Point Extension	Input Point Extension	Output Point Extension
<ul style="list-style-type: none"> ■ DeviceNet Master DVPDNET-SL ■ CANopen Master DVPCOPM-SL 		DVP08SM11N DVP16SM11N	DVP06SN11R DVP08SN11R/T DVP08SN11TS DVP16SN11T DVP16SN11TS
<ul style="list-style-type: none"> ■ Ethernet DVPEN01-SL ■ PROFIBUS-DP Slave DVPPF02-SL 		DVP32SM11N	DVP32SN11TN
<ul style="list-style-type: none"> ■ RS-422/RS-485 Serial Communication Module DVPSCM12-SL ■ BACnet MS/TP Slave Serial Communication Module 			DVP08ST11N
Analog Extension	Analog Extension	Analog Input	Analog Output
<ul style="list-style-type: none"> ■ Analog Input DVP04AD-SL ■ Analog Output DVP04DA-SL 		DVP04AD-S DVP06AD-S DVP04AD-S2	DVP04DA-S DVP02DA-S DVP04DA-S2
Load Cell/Tension	Temperature Measurement	Temperature Control	Remote Temperature Control Module
<ul style="list-style-type: none"> ■ Load Cell Module DVP01LC-SL DVP02LC-SL DVP201LC-SL DVP211LC-SL DVP202LC-SL 	<ul style="list-style-type: none"> ■ Sensor: Pt100, Pt1000 DVP04PT-S DVP06PT-S ■ Sensor: J,K,R,S,T thermocouple DVP04TC-S 	<ul style="list-style-type: none"> New ■ Temperature Control: DVP02TUN-S DVP02TUR-S DVP02TUL-S 	<ul style="list-style-type: none"> New ■ Remote Temperature Control Module: DVP02TKN-S DVP02TKR-S DVP02TKL-S
Communication Modules	Power Supply Modules	Axis Control Module	
<ul style="list-style-type: none"> ■ PROFIBUS Slave DVPPF01-S ■ DeviceNet Slave DV PDT01-S 	<ul style="list-style-type: none"> DVPPS01 DVPPS02 DVPPS05 	<ul style="list-style-type: none"> ■ Single-Axis Positioning DVP01PU-S 	

*1. DVP32EH00R3-L & DVP32EH00T3-L are also compatible with the left-side high-speed extension modules.

*2. Max. quantity of right-side extension module is 14, among which the quantity of -S and -S2 modules must be equal to or less than 8. If the total quantity of extension modules is over 14, applying high density extension modules is recommended.

Specifications

Electrical Specifications

	AC	DC
Power Supply Voltage	100~240V _{AC} (-15%~10%), 50/60Hz ±5%	24V _{DC} (-15%~20%)
Fuse Capacity	2A/250V _{AC}	ES: 2A/250V _{AC} ; SV: 2.5A/30V _{DC}
Spike Voltage Durability	1500V _{AC} (Primary-secondary); 1500V _{AC} (Primary-PE); 500V _{AC} (Secondary-PE)	
Insulation Impedance	>5MΩ (all I/O point-to-ground: 500V _{DC})	
Noise Immunity	ESD: 8kV Air Discharge EFT: Power Line, 2kV Digital I/O: 1kV Analog & Communication I/O: 1kV RS: 26MHz~1GHz, 10V/m	
Earth	The diameter of grounding wire shall not be shorter than that of the power supply cable. (When many PLCs are in use at the same time, please make sure every PLC is properly grounded.)	
Storage/Operation	Storage: -25°C~70°C (temperature); 5%~95% (humidity) Operation: 0°C~55°C (temperature); 5%~95% (humidity); pollution degree 2	

Input Specifications^{*1}

Max. Input Frequency	10 kHz	20 kHz	100 kHz	200 kHz
Input Signal Type	NPN (Sink)/PNP (Source)			
Input Signal Voltage	24V _{DC} ±10% (5mA)			
Response time^{*2}	OFF→ON: 20μs ON→OFF: 50μs	ES/EX/SX/SS2/SX2 OFF→ON: 3.5μs ON→OFF: 20μs	ES2/EX2/SA2/SX2 OFF ON: 2.5μs ON→OFF: 5μs	EH3/SV2/PM OFF→ON: 0.15μs ON→OFF: 3μs

*1. For more detailed specifications, see the "Specification" section in the instruction sheet of each model.

*2. When the input point on PLC conducts only general input functions, use D1020 or D1021 to adjust the response time (default: 10ms).

Output Specifications^{*1}

	Relay-R	Transistor-T		
		General speed	High speed	
Max. Exchange (working) Frequency	1Hz ^{*2}	10 kHz	100 kHz	200 kHz
Current spec.	2A/1 Point	0.3A/point @40°C	SA2/SX2/ES2/EX2/SE	EH3/SV2/PM
			Resistive: 0.5A/point (4A/COM)	Resistive: 0.5A/point (4A/COM)
			Conductive: 12W (24V _{DC}) Light bulb: 2W (24V _{DC})	Conductive: 12W (24V _{DC}) Light bulb: 2W (24V _{DC})
	1.5A/1 Point			
Voltage Spec.	250V _{AC} /30V _{DC}		30V _{DC}	
Response Time	10ms	OFF→ON: 20μs ON→OFF: 30μs	OFF→ON: 2μs ON→OFF: 3μs	OFF→ON: 0.5μs ON→OFF: 2.5μs


*1. For more detailed specifications, see the "Specification" section in the instruction sheet of each model.

*2. Relay life: Resistive load more than 200,000 times; conductive load more than 80,000 times.

Dimensions (unit: mm)


DVP-ES2/EX2 Series

Model Name (mm)	L	L1
DVP16ES200R/T	105	97
DVP20ES200RE	125	117
DVP20ES200TE	125	117
DVP24ES200R/T	125	117
DVP32ES200R/T	145	137
DVP32ES200RC	145	137
DVP32ES200TC	145	137
DVP32ES200RE	165	157
DVP32ES200TE	165	157
DVP32ES211T	145	137
DVP40ES200R/T	165	157
DVP40ES200RE	194	186
DVP40ES200TE	194	186
DVP60ES200R/T	225	217
DVP60ES200RE	255	247
DVP60ES200TE	255	247
DVP80ES200R/T	302	294
DVP20EX200R/T	145	137
DVP30EX200R/T	165	157




DVP-ES2/EX2 Series

Model Name (mm)	L	L1	Type
DVP08XM211N	45	37	①
DVP08XP211R/T	45	37	①
DVP08XN211R/T	45	37	①
DVP16XM211N	70	62	②
DVP16XP211R/T	70	62	②
DVP16XN211R/T	70	62	②
DVP24XP200R/T	145	137	②
DVP24XN200R/T	145	137	②
DVP32XP200R/T	145	137	②
DVP04AD-E2	70	62	②
DVP02DA-E2	70	62	②
DVP04DA-E2	70	62	②
DVP06XA-E2	70	62	②
DVP04PT-E2	70	62	②
DVP04TC-E2	70	62	②
DVP10RC-E2	70	62	②



DVP-PM Series


Model Name (mm)	H	H1	W	W1	W2
DVP20PM00D	90	80	174	164	82
DVP20PM00M	90	80	174	164	82
DVP10PM00M	90	80	143.5	133.5	82



DVP-EH3 Series


Model Name (mm)	H	H1	W	W1	W2
DVP16EH00R3/T3	90	80	113	103	82
DVP20EH00R3/T3	90	80	113	103	82
DVP32EH00M3/MT	90	80	143.5	133.5	82
DVP32EH00R3/T3	90	80	143.5	133.5	82
DVP32EH00R3-L	90	80	143.5	133.5	82
DVP32EH00T3-L	90	80	143.5	133.5	82
DVP40EH00R3/T3	90	80	158.8	153.8	82
DVP48EH00R3/T3	90	80	174	164	82
DVP64EH00R3/T3	90	80	212	202	82
DVP80EH00R3/T3	90	80	276	266	82

*The dimensions of the DVP-EH3 and DVP-EH2 Series are the same.




DVP-SV / SX2 / MC Series

Model Name (mm)	H	H1	W	W1
DVP28SV11R2/T2	60	90	70	53.2
DVP20SX211R/T/S	60	90	70	53.2
DVP10MC11T	60	90	70	53.2



Model Name (mm)	H	H1	W	W1
DVP15MC11T	110	116.2	128	68.4
DVP15MC11T-06	110	116.2	128	68.4
DVP50MC11T	110	116.2	128	68.4
DVP50MC11T-06	110	116.2	128	68.4




DVP-EH3 Series I/O & Extension Modules

Model Name (mm)	H	H1	W	W1	W2
DVP08HM11N	90	80	40	36	82
DVP16HM11N	90	80	55	51	82
DVP32HM11N	90	80	143.5	133.5	82.2
DVP08HN11R/T	90	80	40	36	82
DVP32HN00R/T	90	80	143.5	133.5	82.2
DVP08HP11R/T	90	80	40	36	82
DVP16HP11R/T	90	80	55	51	82
DVP32HP00R/T	90	80	143.5	133.5	82.2
DVP48HP00R/T	90	80	174	164	82.2


Model Name (mm)	H	H1	W	W1	W2
DVP04AD-H2	90	80	60	56	82
DVP04DA-H2	90	80	60	56	82
DVP06XA-H2	90	80	60	56	82
DVP04PT-H2	90	80	60	56	82
DVP04TC-H2	90	80	60	56	82
DVP01PU-H2	90	80	60	56	82
DVPDT02-H2	90	80	40	46	82
DVPCP02-H2	90	80	40	46	82
DVPPF02-H2	90	80	40	46	82
DVP04AD-H3	90	80	60	56	82
DVP04DA-H3	90	80	60	56	82
DVP06XA-H3	90	80	60	56	82

*The dimensions of the DVP-EH3 and DVP-EH2 Series are the same.




DVP-SE / SX / SS2 / SA2 Series

Model Name (mm)	H	H1	W	W1
DVP28SS211R/T	96	90	46	60
DVP28SA211R/T	96	90	46	60
DVP26SE11R/T	96	90	46	60
DVP14SS211R/T	96	90	25.2	60
DVP12SS211S	96	90	25.2	60
DVP12SA211R/T	96	90	37.4	60
DVP12SE11R/T	96	90	37.4	60
DVP10SX11R/T	96	90	37.4	60




High-Speed Extension Modules (left-side)

Model Name (mm)	H	H1	W	W1
DVPEN01-SL	96	90	33.1	60
DVPCOPM-SL	96	90	33.1	60
DVPDNET-SL	96	90	33.1	60
DVPPF02-SL	96	90	33.1	60
DVPSCM12-SL	96	90	33.1	60
DVPSCM52-SL	96	90	33.1	60
DVP04AD-SL	96	90	33.1	60
DVP04DA-SL	96	90	33.1	60
DVP01LC-SL	96	90	33.1	60
DVP02LC-SL	96	90	33.1	60
DVP201LC-SL	96	90	33.1	60
DVP202LC-SL	96	90	33.1	60
DVP211LC-SL	96	90	33.1	60




Remote I/O Modules

Model Name (mm)	H	H1	W	W1
RTU-DNET	96	90	25.2	60
RTU-485	96	90	25.2	60
RTU-EN01	96	90	25.2	60
RTU-PD01	96	90	25.2	60




Remote Temperature Control Modules

Model Name (mm)	H	H1	W	W1
DVP02TKN-S	96	90	25.2	60
DVP02TKR-S	96	90	25.2	60
DVP02TKL-S	96	90	25.2	60




DVP-PS01/02 Power Supply Modules

Model Name (mm)	H	H1	W	W1
DVPPS01	100	90	36.5	60
DVPPS02	100	90	55	60




DVP-PS05 Power Supply Modules

Model Name (mm)	H	H1	W	W1
DVPPS05	93.3	90	60	63.4




PIN Definition of UC-MS030-01A




DVP-S Series I/O and Extension Modules

Model Name (mm)	H	H1	W	W1
DVP08SM11N	96	90	25.2	60
DVP06SN11R	96	90	25.2	60
DVP08SN11R/T/TS	96	90	25.2	60
DVP08SP11R/T/TS	96	90	25.2	60
DVP16SP11R/T/TS	96	90	25.2	60
DVP16SN11T	96	90	25.2	60
DVP16SN11TS	96	90	25.2	60
DVP04AD-S	96	90	25.2	60
DVP04AD-S2	96	90	25.2	60
DVP06AD-S	96	90	25.2	60
DVP02DA-S	96	90	25.2	60
DVP04DA-S	96	90	25.2	60
DVP04DA-S2	96	90	25.2	60
DVP06XA-S	96	90	25.2	60
DVP06XA-S2	96	90	25.2	60
DVP04PT-S	96	90	25.2	60
DVP06PT-S	96	90	25.2	60
DVP04TC-S	96	90	25.2	60
DVP01PU-S	96	90	25.2	60
DVPPF01-S	96	90	25.2	60
DVPDT01-S	96	90	25.2	60
DVP02TUN-S	96	90	25.2	60
DVP02TUR-S	96	90	25.2	60
DVP02TUL-S	96	90	25.2	60




Model Name (mm)	H	H1	W	W1
DVP32SN11TN	96	90	25.2	60
DVP32SM11N	96	90	25.2	60



PLC Editing Software: ISPSoft V2.0

Highly Accessible Programming Software with Fully Integrated Interface


Advanced Programming Interface + Visualized Hardware Configuration + Simplified Network Configuration




Advanced Programming Interface

Project Management Window


- **New functions:** Network configuration (NWCONFIG), hardware configuration (HWCONFIG) and PLC card utility
- 5 programming languages for programs and function blocks (FB): LD / FBD / SFC / IL / ST
- **Function Blocks:** Symbols can be introduced in call-by-value or call-by-reference types. Function blocks can be called in a function block for up to 32 levels
- **Monitor Table:** It can be stored and managed separately. Multiple monitor tables can be stored in a single project
- **User Library:** Users can design frequently used instructions for specific applications in different industries
- **Task:** Supports cyclic, I/O interrupt, timer interrupt, external interrupt, and more. Software will provide the usable tasks for different CPUs
- Built-in Delta Function Blocks provide a convenient programming environment for operators



Visualized Hardware Configuration



Simplified Network Configuration



4-Line Text Panel HMI

TP04G-AL-C

TP04G-AL2

- ▶ 4.1" STN-LCD
- ▶ User-defined function keys available
- ▶ Supports RS-232/RS-422/RS-485 ports (TP04G-AL2)
- ▶ Password protection function available
- ▶ User-defined boot screen available
- ▶ Built-in real time clock (RTC)

Dimensions	4.1" (101.8 × 35.24 mm)
Resolution	192 × 64
Display Color	Monochrome
Flash Memory	256k bytes
Function Key	10 function keys
Password	Available
Recipe Function	Not available
RTC	Available
Serial COM Port	RS-232 & RS-422/485
Editing Software	TPEditor

4-Line Text Panel HMI

TP04G-BL-C

- ▶ 4.1" STN-LCD
- ▶ 0~9 numeric keys and user-defined function available
- ▶ Built-in RS-232 and RS-422/RS-485 ports
- ▶ Supports MODBUS ASCII/RTU modes
- ▶ Password protection function available
- ▶ User-defined boot screen available
- ▶ Built-in real time clock (RTC)

Dimensions	4.1" (101.8 × 35.24 mm)
Resolution	192 × 64
Display Color	Monochrome
Flash Memory	256k bytes
Function Key	17 function keys
Password	Available
Recipe Function	Not available
RTC	Available
Serial COM Port	RS-232 & RS-422/485
Editing Software	TPEditor

8-Line Text Panel HMI

TP08G-BT2

- ▶ 3.8" STN-LCD
- ▶ Resolution: 240x128 dots
- ▶ Built-in 1,024KB flash memory
- ▶ 24 user-defined function keys
- ▶ Built-in RS-232 and RS-422/RS-485 ports
- ▶ Supports recipes and macro functions

Dimensions	3.8" (83 x 41 mm)
Resolution	240 × 128
Display Color	Monochrome
Flash Memory	1 M bytes
Function Key	24 function keys
Password	Available
Recipe Function	Available
RTC	Available
Serial COM Port	RS-232 & RS-422/485
Editing Software	TPEditor

Applications

Intelligent control systems for aquaculture, steel sleeve tapping machines, air compressors, plant factories

7-Inch Touch Panel HMI with Built-in PLC

TP70P-RM0

- ▶ Adopts the core of the DVP-SS2 Series PLC:
program capacity: 2k steps / D device: 5k words
- ▶ 7" TFT-LCD
- ▶ Touch screen
- ▶ Built-in USB port for program upload/download
- ▶ Built-in RS-232 and RS-485 ports
- ▶ Supports MODBUS ASCII/RTU modes
- ▶ Built-in real time clock (RTC)

Dimensions	7" (154 × 85 mm)
Resolution	800 × 480
Display Color	65,535 colors
Flash Memory	64 M bytes
Function Key	Not available
Password	Available
Recipe Function	Not available
RTC	Available
Serial COM Port	RS-232 & RS-485
Editing Software	TPEditor

7-Inch Touch Panel HMI with Built-in PLC

TP70P

- ▶ Adopts the core of the DVP-SS2 Series PLC:
program capacity: 4k steps / D device: 5k words
- ▶ Provides 2 sets of 10kHz high-speed pulse input
- ▶ 7" TFT-LCD
- ▶ Touch screen
- ▶ Built-in USB port for program upload/download
- ▶ Built-in RS-485 port*2
- ▶ Supports MODBUS ASCII/RTU modes
- ▶ Built-in real time clock (RTC)
- ▶ Digital and analog I/O terminals available

Dimensions	7" (154 × 85 mm)
Resolution	800 × 480
Display Color	65,535 colors
Flash Memory	64 M bytes
Function Key	Not available
Password	Available
Recipe Function	Not available
RTC	Available
Serial COM Port	2 sets of RS-485
Editing Software	TPEditor

4-Line Text Panel HMI with Built-in PLC

TP04P











- ▶ Adopts the core of the DVP-SS2 Series PLC:
program capacity: 8k steps / D device: 5k words
- ▶ Provides 2 sets of 10kHz high-speed pulse input
(Excludes TP04P-08TP1R)
- ▶ 4.1" STN-LCD
- ▶ Provides 0~9 numeric keys with user-defined function
- ▶ Built-in USB port for program upload/download
- ▶ Built-in RS-485 port*2
- ▶ Supports MODBUS ASCII/RTU modes
- ▶ User-defined boot screen available
- ▶ Built-in real time clock (RTC)
- ▶ Digital and analog I/O terminals available

Dimensions	4.1" (101.8 × 35.24 mm)
Resolution	192 × 64
Display Color	Monochrome
Flash Memory	1 M bytes
Function Key	17 function keys
Password	Available
Recipe Function	Not available
RTC	Available
Serial COM Port	2 sets for RS-485
Editing Software	TPEditor

		Text Panel HMI						Text/Touch Panel HMI with Built-in PLC				
Model		TP02G-AS1	TP04G-AS2	TP08G-BT2	TP04G-AL-C	TP04G-AL2	TP04G-BL-C	TP04P-Series	TP04P-08TP1R	TP70P-Series		
Display Specifications	Screen Type	STN-LCD						TFT-LCD				
	Display Color	Monochrome						65,535				
	Resolution	160 x 32	128 x 64	240 x 128	192 x 64			800 x 480				
	Backlight	Life span of backlight is about 50,000 hours at 25°C						20,000 hours				
	Display Range	72 x 22 mm (67 x 32 mm)	3" (83 x 41 mm)	3.8" (83 x 41 mm)	4.1" (101.8 x 35.24 mm)			7" (154 x 85 mm)				
Flash Memory		256k bytes		1M bytes	256k bytes		1M bytes		64M bytes			
Program Download Port		COM1 (RS-232)						COM1 (USB)		USB		
Serial COM Port	COM1	RS-232	RS-232/422		RS-232	RS-232/422	RS-232	-				
	COM2	RS-485			-	RS-422/485	RS-422/485	RS-485				
	COM3	-			-	-	-	RS-485				
Extension Interface		The slot for program copy card						-				
Real-time Clock		-	Built-in						-			
Auxiliary Keys	System Keys	6	7	12	5	7	5	-				
	Function Keys	10	5	12	5	10	5	-				
Operating Voltage		+24V _{DC} (-10% ~ +20%)						-				
Backup Battery		3V lithium battery CR2032 x 1/battery life: 5 years						-				
Buzzer		85 dB						-				
Cooling Method		Natural air circulation						-				
Operating Temperature		0 °C ~ 50 °C						-				
Storage Temperature		-20 °C ~ +60 °C						-				
Operating Humidity		10% ~ 90% RH (0 ~ 40 °C)						-				
Vibration		IEC 61131-2, IEC 68-2-6 (TEST Fc); 5 Hz ≤ f < 8.4 Hz Continuous: 3.5 mm; 8.4 Hz ≤ f ≤ 150 Hz Continuous: 1.0 g						-				
Shock		IEC 61131-2, IEC 68-2-27 (TEST Ea); 15g peak, 11ms duration, half-sine, three shocks in each direction per axis, on 3 mutually perpendicular axes (total of 18 shocks)						-				
Radiated Emission		CISPR11, Class A Frequency: 30 ~ 230 MHz, Limits: 40 dB uV/m Frequency: 230 MHz ~ 1 GHz, Limits: 47 dB uV/m						-				
Radiated Electromagnetic Field		EN61000-4-3, Frequency: 80 ~ 2000 MHz, Limits: 10 V/m						-				
Electrostatic Discharge		EN61000-4-2, Air Discharge: 8 KV, Contact Discharge: 4 KV						-				
Fast Transient Burst		EN61000-4-4, Power Line: 1 KV, Communication I/O: 500 V						-				
Dimensions (Width (W) × Height (H) × Depth (D))		147 x 97 x 35.5	210 x 122 x 45	163.6 x 108.6 x 37	175.8 x 108.8 x 37	TP04P Series: 175.8 x 108.6 x 59.2 TP04P-20EXL1T: 175.8 x 108.6 x 82.4		175.8 x 108.6 x 37	TP70P Series: 205.6 x 142.6 x 49 TP70P-RM0: 205.6 x 142.6 x 37 TP70P-211LC1T: 205.6 x 142.6 x 87.7			
Panel Cutout		136 x 85	196 x 108	151 x 96	163 x 96	163 x 96			191 x 128			
Weight		240 g	430 g	268 g	270 g	292 g	TP04P Series: 500 g TP04P-20EXL1T: 650 g	333 g	TP70P Series: 680 g TP70P-RM0: 620 g TP70P-211LC1T: 900 g			
Safety Approvals (Waterproof Class of Front Panel)		IP65/NEMA4 & CE, UL Type 4 indoor						IP65/NEMA4 & CE, UL				
Editing Software		TPEditor V1.87						-				

Product Outline and Dimensions

Unit: mm

TP02G-AS1	TP04G-AS2	TP04G-AL-C/TP04G-AL2	TP04G-BL-C
  	  	  	  
TP04P-Series (Exclude TP04P-08TP1R, TP04P-20EXL1T)	TP08G-BT2	TP70P-Series (Exclude TP70P-RM0, TP70P-211LC1T)	TP70P-RM0
  	  	  	  
TP04P-08TP1R	TP04P-20EXL1T	TP70P-211LC1T	
  	  	  	

DVP Series Model Name Instructions

• PLC	• DI/DO Module	• AI/AO Module
<p>Series ① ② ③ ④ ⑤</p>	<p>Series ① ② ③ ④ ⑤</p>	<p>Series ① ② ③</p>
1. Total I/O 2. Model ES/ES2: DVP-ES/ES2 series PLC EX/EX2: DVP-EX/EX2 series PLC SS/SS2: DVP-SS/SS2 series PLC SA/SA2: DVP-SA/SA2 series PLC SX/SX2: DVP-SX/SX2 series PLC SC: DVP-SC series PLC SV: DVP-SV series PLC SE: DVP-SE series PLC PM: DVP-PM series PLC MC: DVP-MC series PLC EH: DVP-EH series PLC EC: DVP-EC series PLC 3. Power supply 00: AC power input 11: DC power input 4. Output type R: Relay T: Transistor (NPN) M: Mixed with differential signal S: Transistor (PNP) RC: Relay + CANopen TC: Transistor + CANopen RE: Relay + Ethernet TE: Transistor + Ethernet 5. Version	1. Total I/O 2. Model X: DVP-ES/EX/ES2/EX2 series PLC S: DVP-SS/SA/SX/SC/SV/SS2/ SA2/ SX2/SV2/SE/MC series PLC H: DVP-EH2/EH3/PM series PLC 3. I/O type M: Input point N: Output point P: Input + output 4. Power supply 00: AC power input 11: DC power input 5. Output type R: Relay T: Transistor (NPN) TS: Transistor (PNP) N: None output	1. Total I/O 2. Module function AD: Analog/digital conversion DA: Digital/analog conversion PT: PT type temperature module TC: Thermocouple type temperature Module XA: AD+DA module LC: Load cell module RC: Resolver module 3. Compatible model S or S2: DVP-SS/SA/SX/SC/SV/SS2/ SA2/SX2/SV2/SE/MC Series PLC SL: left-side extension for DVP-S Series PLC E2: DVP-ES2/EX2 Series PLC
• PI/PO Module	• Function Card	• Network Module
<p>Series ① ② ③</p>	<p>Series ① ② ③</p>	<p>Series ① ②</p>
1. Total I/O 2. Module function HC: High-speed counter PU: Single-axis positioning module 3. Compatible model S: DVP-SS/SA/SX/SC/SV/SS2/SA2/ SX2/SV2/SE/MC Series PLC H2/H3: DVP-EH2/EH3/PM Series PLC SL: left-side extension for DVP-S Series PLC	1. Function Card 2. Function 232: RS-232 card 422: RS-422 card 485: RS-485 card 2AD: 2ch analog input 2DA: 2ch analog output 3. Particular definition S: Slave mode (applicable to COM3 coding only)	1. Module function EN01: MODBUS TCP DNET: DeviceNet master COPM: CANopen master CP02: CANopen Slave DT01/02: DeviceNet Slave PF01/02: PROFIBUS DP Slave 2. Compatible model S: DVP-SS/SA/SX/SC/SV/SS2/ SA2/SX2/SV2/SE/MC Series PLC H2/H3: DVP- EH2/EH3/PM Series PLC SL: left-side extension for DVP-S Series PLC
• Remote I/O	• Accessory: Cable	• Accessory: Other
<p>Series ①</p>	<p>Series ① ② ③ ④</p>	<p>Series ① ② ③</p>
1. Type DNET: DeviceNet 485: RS-485 EN01: MODBUS TCP	1. Accessory 2. Accessory definition CAB: Cable 3. Type 1, 2, 3, 4, 4. Cable length 15: 1.5 m 30: 3.0 m	1. Accessory 2. Accessory definition Bt: Battery 3. Type: 01, 02

*For the availability of the product models, please contact Delta sales representatives or refer to "Ordering Information" in this catalogue.

DVP Series PLC Function Overview

Select your desired specifications and locate the most suitable PLC.



Item	Specifications	Check	Model							
			ES2	EX2	EH3	SS2	SA2	SX2	SV2	SE
Power Supply	AC	<input type="checkbox"/>	○	○	○					
	DC	<input type="checkbox"/>				○	○	○	○	○
I/O Points	< 256	<input type="checkbox"/>	△	△						
	< 512	<input type="checkbox"/>			△	△	△	△	△	△
Program Capacity	< 8 k	<input type="checkbox"/>				○				
	< 16 k	<input type="checkbox"/>	○	○			○	○		○
	< 32 k	<input type="checkbox"/>			○				○	
Output Type	Transistor (NPN)	<input type="checkbox"/>	○	○	○	○	○	○	○	○
	Transistor (PNP)	<input type="checkbox"/>				○	△	○	○	△
	Relay	<input type="checkbox"/>	○	○	○	○	○	○	○	○
	Differential signal	<input type="checkbox"/>			○					
Communication	3 COM ports (RS-232/485)	<input type="checkbox"/>	○	○	△		○	△	△	△
	Ethernet	<input type="checkbox"/>	○		△		△	△	△	○
	USB	<input type="checkbox"/>						○		○
	DeviceNet	<input type="checkbox"/>			△*1		△*1	△*1	△*1	△*1
	CANopen	<input type="checkbox"/>			△*1		△*1	△*1	△*1	△*1
	PROFIBUS	<input type="checkbox"/>			△*1		△*1	△*1	△*1	△*1
Positioning	2-axis output	<input type="checkbox"/>	○	○	○	○	○	○		○
	4-axis output	<input type="checkbox"/>			○				○	
	> 4 axes	<input type="checkbox"/>			△	△	△	△	△	△
	2-axis interpolation	<input type="checkbox"/>	○	○	○		○	○	○	○
	100 kHz high speed	<input type="checkbox"/>	○	○			○	○		○
	200 kHz high speed	<input type="checkbox"/>			○	△	△	△	○	△
High-speed Counting	≤ 2 channels	<input type="checkbox"/>	○	○		○	○	○		○
	≥ 3 channels	<input type="checkbox"/>			○*3	△	△	△	○	△
	100 kHz high speed	<input type="checkbox"/>	○	○			○	○		○
	200 kHz high speed	<input type="checkbox"/>			○	△	△	△	○	△
Analog Function	< 4 channels (AD)	<input type="checkbox"/>	△	○	△	△	△	○	△	△
	< 2 channels (DA)	<input type="checkbox"/>	△	○*2	△	△	△	○*2	△	△

Note:

○ With such specification ○ Varies upon model △ With such specification when connected to extension module/function card

*1: Series that support left-side modules can support both master and slave; other series support only slave

*2: DVP-EX / SX2 Series have 4 channels of analog input and 2 channels of analog output

*3: In addition to the built-in 4 channels of high-speed counters, the DVP-EH3 Series can connect high-speed counter modules

Ordering Information

DVP-EC3 Series PLC

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
DVP-EC3 Series Basic PLC	100~240V _{AC}	Relay	6	4	DVP10EC00R3	 
	100~240V _{AC}	Transistor	6	4	DVP10EC00T3	
	100~240V _{AC}	Relay	8	6	DVP14EC00R3	
	100~240V _{AC}	Transistor	8	6	DVP14EC00T3	
	100~240V _{AC}	Relay	8	8	DVP16EC00R3	
	100~240V _{AC}	Transistor	8	8	DVP16EC00T3	
	100~240V _{AC}	Relay	12	8	DVP20EC00R3	
	100~240V _{AC}	Transistor	12	8	DVP20EC00T3	
	100~240V _{AC}	Relay	12	12	DVP24EC00R3	
	100~240V _{AC}	Transistor	12	12	DVP24EC00T3	
	100~240V _{AC}	Relay	18	12	DVP30EC00R3	
	100~240V _{AC}	Transistor	18	12	DVP30EC00T3	

DVP-EC3 Series PLC

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
DVP-EC3 Series Basic PLC	100~240V _{AC}	Relay	16	16	DVP32EC00R3	 
	100~240V _{AC}	Transistor	16	16	DVP32EC00T3	
	100~240V _{AC}	Relay	24	16	DVP40EC00R3	
	100~240V _{AC}	Transistor	24	16	DVP40EC00T3	
	100~240V _{AC}	Relay	28	20	DVP48EC00R3	
	100~240V _{AC}	Transistor	28	20	DVP48EC00T3	
	100~240V _{AC}	Relay	36	24	DVP60EC00R3	
	100~240V _{AC}	Transistor	36	24	DVP60EC00T3	

Fastest execution time of basic instructions 3.8 μs Execution time of MOV instruction 5.04 μs

DVP-ES2/EX2 Series PLC

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
DVP-ES2 Series Standard PLC	100~240V _{AC}	Relay	8	8	DVP16ES200R	 
	100~240V _{AC}	Transistor	8	8	DVP16ES200T	
	100~240V _{AC}	Relay	16	8	DVP24ES200R	
	100~240V _{AC}	Transistor	16	8	DVP24ES200T	
	100~240V _{AC}	Relay	16	16	DVP32ES200R	
	100~240V _{AC}	Transistor	16	16	DVP32ES200T	
	24V _{DC}	Transistor	16	16	DVP32ES211T	
	100~240V _{AC}	Relay	24	16	DVP40ES200R	
	100~240V _{AC}	Transistor	24	16	DVP40ES200RM ^{*1}	
	100~240V _{AC}	Relay	36	24	DVP60ES200R	
	100~240V _{AC}	Transistor	36	24	DVP60ES200T	
	100~240V _{AC}	Relay	40	40	DVP80ES200R	
	100~240V _{AC}	Transistor	40	40	DVP80ES200T	
DVP-ES2 Series Standard PLC with Built-in CANopen	100~240V _{AC}	Relay	16	16	DVP32ES200RC	
	100~240V _{AC}	Transistor	16	16	DVP32ES200TC	
New DVP-ES2 Series Standard PLC with Ethernet Communication	100~240V _{AC}	Relay	12	8	DVP20ES200RE	
	100~240V _{AC}	Transistor	12	8	DVP20ES200TE	
	100~240V _{AC}	Relay	16	16	DVP32ES200RE	
	100~240V _{AC}	Transistor	16	16	DVP32ES200TE	
	100~240V _{AC}	Relay	24	16	DVP40ES200RE	
	100~240V _{AC}	Transistor	24	16	DVP40ES200TE	
	100~240V _{AC}	Relay	36	24	DVP60ES200RE	
	100~240V _{AC}	Transistor	36	24	DVP60ES200TE	
DVP-EX2 Series Analog PLC	100~240V _{AC}	Relay	8	6	DVP20EX200R	
	100~240V _{AC}	Analog	4	2	DVP20EX200T	
DVP-EX2 Series Temperature/Analog PLC	100~240V _{AC}	Transistor	8	6	DVP30EX200R	
	100~240V _{AC}	Analog	4	2	DVP30EX200T	
	100~240V _{AC}	Relay	16	10	DVP30EX200R	
	100~240V _{AC}	Transistor	16	10	DVP30EX200T	
Fastest execution time of basic instructions			0.35 μs	Execution time of MOV instruction		3.4 μs

*1: Built-in SD card slot

DVP-ES2/EX2 Series Digital I/O Module (AC power supply)

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
Digital Module	100~240V _{AC}	Relay	-	24	DVP24XN200R	 
	100~240V _{AC}	Transistor	-	24	DVP24XN200T	
	100~240V _{AC}	Relay	16	8	DVP24XP200R	
	100~240V _{AC}	Transistor	16	8	DVP24XP200T	
	100~240V _{AC}	Relay	16	16	DVP32XP200R	
	100~240V _{AC}	Transistor	16	16	DVP32XP200T	

Ordering Information

DVP-ES2/EX2 Series Digital/Analog/Special Module (24V_{DC})

Product Name	Output Method	Inputs	Outputs	Model Name	Certificates	
Digital Module	-	8	-	DVP08XM211N	 	
	Relay	-	8	DVP08XN211R		
	Transistor	-	8	DVP08XN211T		
	Relay	4	4	DVP08XP211R		
	Transistor	4	4	DVP08XP211T		
	-	16	-	DVP16XM211N		
	Relay	-	16	DVP16XN211R		
	Transistor	-	16	DVP16XN211T		
	Relay	8	8	DVP16XP211R		
	Transistor	8	8	DVP16XP211T		
Analog I/O Module	<ul style="list-style-type: none"> 4 points of analog voltage (10V, 5V)/current (20mA, 0~20mA, 4~20mA) input ^{**1} Resolution: 14-bit (-32,000~+32,000) 				DVP04AD-E2	
	<ul style="list-style-type: none"> 4 points of analog voltage (-10V~+10V)/current (0~20mA, 4~20mA) output^{**1} Resolution: 14-bit (-32,000~+32,000)/(0~+32,000) 				DVP04DA-E2	
	<ul style="list-style-type: none"> 2 points of analog voltage (-10V~+10V)/current (0~20mA, 4~20mA) output^{**1} Resolution: 14-bit (-32,000~+32,000)/(0~+32,000) 				DVP02DA-E2	
	<ul style="list-style-type: none"> 4 points of analog voltage (10V, 5V)/current (20mA, 0~20mA, 4~20mA) input ^{**1} Input resolution: 14-bit (-32,000~+32,000) 				DVP06XA-E2	
	<ul style="list-style-type: none"> 2 points of analog voltage (-10V~+10V)/current (0~20mA, 4~20mA) output Output resolution: 14-bit (-32,000~+32,000)/(0~+32,000) 					
Temperature Measurement Module	<ul style="list-style-type: none"> 4 points of platinum RTD (Pt100, Pt1000, Ni100, Ni1000) sensor input/0~300Ω resistance input ^{**1} Resolution: 16-bit With PID temperature control 				DVP04PT-E2	
	<ul style="list-style-type: none"> 4 points of thermocouple (J, K, R, S, T, E, N Type) sensor input/-80mV~+80mV voltage input ^{**1} Resolution: 20-bit With PID temperature control 				DVP04TC-E2	
Absolute Resolver Module	<ul style="list-style-type: none"> Converts 1 set of resolver input signal (angle/speed) into digital signals Resolution: 12-bit Supports disconnection detection for distance up to 50m 				DVP10RC-E2	
Extension module	<ul style="list-style-type: none"> Extends distance between the I/O modules of the DVP-ES2 Series within a given distance 				DVPAEXT01-E2	

^{**1}. Digital/analog photocoupler isolation. No isolation among channels.

DVP-EH3 Series PLC

Product name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
DVP-EH3 Series High Performance PLC	100~240V _{AC}	Relay	8	8	DVP16EH00R3	 
	100~240V _{AC}	Transistor	8	8	DVP16EH00T3	
	100~240V _{AC}	Relay	12	8	DVP20EH00R3	
	100~240V _{AC}	Transistor	12	8	DVP20EH00T3	
	100~240V _{AC}	Transistor	16	16	DVP32EH00T3	
	100~240V _{AC}	Relay	16	16	DVP32EH00R3	
	100~240V _{AC}	Differential + Relay	16	16	DVP32EH00M3	
	100~240V _{AC}	Differential + Transistor	16	16	DVP32EH00MT	
	100~240V _{AC}	Relay	16	16	DVP32EH00R3-L	
	100~240V _{AC}	Transistor	16	16	DVP32EH00T3-L	
	100~240V _{AC}	Transistor	24	16	DVP40EH00T3	
	100~240V _{AC}	Relay	24	16	DVP40EH00R3	
	100~240V _{AC}	Relay	24	24	DVP48EH00R3	
	100~240V _{AC}	Transistor	24	24	DVP48EH00T3	
	100~240V _{AC}	Relay	32	32	DVP64EH00R3	
	100~240V _{AC}	Transistor	32	32	DVP64EH00T3	
	100~240V _{AC}	Relay	40	40	DVP80EH00R3	
	100~240V _{AC}	Transistor	40	40	DVP80EH00T3	
Execution time of basic instructions				0.24 μs		

DVP-EH3 Series Digital/Analog Module

Product Name	Output Method	Inputs	Outputs	Model Name	Certificates
Digital Module	Relay	4	4	DVP08HP11R	 
	Transistor	4	4	DVP08HP11T	
	Relay	-	8	DVP08HN11R	
	Transistor	-	8	DVP08HN11T	
	-	8	-	DVP08HM11N	
	Relay	8	8	DVP16HP11R	
	Transistor	8	8	DVP16HP11T	
	-	16	-	DVP16HM11N	
	-	32	-	DVP32HM11N	
	Relay	-	32	DVP32HN00R	
	Transistor	-	32	DVP32HN00T	
	Relay	16	16	DVP32HP00R	
	Transistor	16	16	DVP32HP00T	
	Relay	24	24	DVP48HP00R	
	Transistor	24	24	DVP48HP00T	
Analog Module	<ul style="list-style-type: none"> 4 points of analog voltage (-10V~+10V)/current (-20mA~+20mA)^{**} Input resolution: 14-bit Built-in RS-485 interface 				DVP04AD-H2
	<ul style="list-style-type: none"> 4 points of analog voltage (0V~+10V)/current (0mA~+20mA) output^{**} Resolution: 12-bit Built-in RS-485 interface 				DVP04DA-H2
	<ul style="list-style-type: none"> 4 points of analog voltage (-10V~+10V)/current (-20mA~+20mA) input 2 points of analog voltage (0V~+10V)/current (0mA~+20mA) output Resolution: 12-bit Built-in RS-485 interface 				DVP06XA-H2
	<ul style="list-style-type: none"> 4 points of platinum RTD (Pt100, Pt1000, Ni100, Ni1000) sensor input^{**}/ 0~300Ω or 0~3000Ω resistance input Resolution: 0.1°C Built-in RS-485 interface 				DVP04PT-H2
	<ul style="list-style-type: none"> 4 points of thermocouple (J, K, R, S, T, E, N Type) sensor input^{**}/ 0~150mV voltage input Resolution: 0.1°C Built-in RS-485 interface 				DVP04TC-H2
	<ul style="list-style-type: none"> 8 points of thermocouple (J, K, R, S, T, E, N Type) sensor input^{**}/ 0~150mV or ±150mV voltage input Resolution: 0.1°C Built-in RS-485 interface 				DVP08TC-H2
	<ul style="list-style-type: none"> 4 channels of differential voltage (-10V~+10V)/current (-20mA~+20mA) input Resolution: 16-bit Built-in RS-485 interface 				DVP04AD-H3
	<ul style="list-style-type: none"> 4 channels of voltage (-10V~+10V)/current (0~+20mA) output Resolution: 16-bit Built-in RS-485 interface 				DVP04DA-H3
	<ul style="list-style-type: none"> 4 channels of differential voltage (-10V~+10V)/current (-20mA~+20mA) input 2 channels of voltage (-10V~+10V)/current (0~+20mA) output Resolution: 16-bit Built-in RS-485 interface 				DVP06XA-H3
	<ul style="list-style-type: none"> 2 points of analog voltage (0~10V)/current (0~20mA) input Resolution: 12-bit 				

*1. Digital/analog photocoupler isolation. No isolation among channels.

DVP-EH3 Series Extension Module/Function Card

Product Name	Description	Model Name	Certificates
Positioning Module	Servo position control module (single axis, 200 kHz)	DVP01PU-H2	 
High-Speed Counter	High-speed counter module (1CH)	DVP01HC-H2	
Communication Module	PROFIBUS DP slave communication module	DVPPF02-H2	
	CANopen slave communication module	DVPCP02-H2	
	DeviceNet slave communication module	DVPDT02-H2	
Function Card	RS-232 port conversion (DVP-EH2: COM2; DVP-EH3: COM3)	DVP-F232	 
	RS-422 port conversion (DVP-EH2: COM2; DVP-EH3: COM3)	DVP-F422	
	RS-485 port extension (COM3) (DVP-EH3 only)	DVP-F485	
	<ul style="list-style-type: none"> 2 points of analog voltage (0~10V)/current (0~20mA) input Resolution: 12-bit 	DVP-F2AD	
	<ul style="list-style-type: none"> 2 points of analog voltage (0~10V)/current (0~20mA) output Resolution: 12-bit 	DVP-F2DA	
	Ethernet communication card (compatible with controllers built-in with 32 I/O and above)	DVP-FEN01	

Ordering Information

DVP-S Series PLC

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
DVP-SV2 Series Functional Slim PLC	24V _{DC}	Relay	16	12	DVP28SV11R2	 
	24V _{DC}	Transistor	16	12	DVP28SV11T2	
	24V _{DC}	Transistor (PNP)	16	12	DVP28SV11S2	
	24V _{DC}	Transistor	10 (2AI)	12	DVP24SV11T2	
Execution time of basic instructions			0.24 μs			
DVP-SS2 Series Standard Slim PLC	24V _{DC}	Relay	16	12	DVP28SS211R New	 
	24V _{DC}	Transistor	16	12	DVP28SS211T New	
	24V _{DC}	Relay	8	6	DVP14SS211R	
	24V _{DC}	Transistor	8	6	DVP14SS211T	
	24V _{DC}	Transistor(PNP)	8	4	DVP12SS211S	
DVP-SA2 Series Advanced Slim PLC	24V _{DC}	Relay	16	12	DVP28SA211R New	 
	24V _{DC}	Transistor	16	12	DVP28SA211T New	
	24V _{DC}	Relay	8	4	DVP12SA211R	
	24V _{DC}	Transistor	8	4	DVP12SA211T	
DVP-SX2 Series Analog Slim PLC	24V _{DC}	Relay	8 (4AI)	6 (2AO)	DVP20SX211R	
	24V _{DC}	Transistor	8 (4AI)	6 (2AO)	DVP20SX211T	
	24V _{DC}	Transistor (PNP)	8 (4AI)	6 (2AO)	DVP20SX211S	
Fastest execution time of basic instructions		0.35 μs	Execution time of MOV instruction		3.4 μs	
DVP-SE Series Network Type Slim PLC	24V _{DC}	Relay	14	12	DVP26SE11R ^(*) New	 
	24V _{DC}	Transistor	14	12	DVP26SE11T ^(*) New	
	24V _{DC}	Relay	8	4	DVP12SE11R	
	24V _{DC}	Transistor	8	4	DVP12SE11T	
Fastest execution time of basic instructions		0.64 μs	Execution time of MOV instruction		2 μs	
DVP-SX Series Analog Slim PLC	24V _{DC}	Relay	4 (2AI)	2 (2AO)	DVP10SX11R	 
	24V _{DC}	Transistor	4 (2AI)	2 (2AO)	DVP10SX11T	
Fastest execution time of basic instructions		3.8 μs	Execution time of MOV instruction		5.04 μs	

Note 1: Please contact our distributors for release date

DVP-S Series Digital/Analog Module

Product name	Output Method	Inputs	Outputs	Model Name	Certificates
Digital Module	Relay	-	6	DVP06SN11R	 
	Relay	-	8	DVP08SN11R	
	Transistor	-	8	DVP08SN11T	
	Transistor	-	16	DVP16SN11T	
	Relay	4	4	DVP08SP11R	
	Transistor	4	4	DVP08SP11T	
	-	8	-	DVP08SM11N	
	-	8	-	DVP08SM10N	
	Transistor (PNP)	-	8	DVP08SN11TS	
	Digital switch	8	-	DVP08ST11N	
	Relay	8	8	DVP16SP11R	
	Transistor (PNP)	4	4	DVP08SP11TS	
	Transistor (NPN)	8	8	DVP16SP11T	
	Transistor (PNP)	8	8	DVP16SP11TS	
	Transistor (PNP)	-	16	DVP16SN11TS	
	-	16	-	DVP16SM11N	
	Transistor, MIL	-	32	DVP32SN11TN	
	MIL	32	-	DVP32SM11N	
Product Name	Description			Model Name	Certificates
Analog I/O Module	▪ 4 points of analog input voltage (-10V ~ +10V) / current (-20mA ~ +20mA) ▪ Input resolution: 14-bit		▪ Built-in RS-485 interface ▪ Differential input		DVP04AD-S2
	▪ 4 points of analog output voltage (0V ~ +10V) / current (0mA ~ +20mA)		▪ Output resolution: 12-bit ▪ Built-in RS-485 interface		DVP04DA-S2
	▪ Analog input+output module (6 points)		▪ Input / output resolution: 12-bit ▪ Built-in RS-485 interface ▪ Differential input		DVP06XA-S2
	▪ 4 points of analog input voltage (-10V ~ +10V) / current (-20mA ~ +20mA)		▪ Input / output resolution: 12-bit ▪ Built-in RS-485 interface ▪ Differential input		
	▪ 2 points of analog output voltage (0V ~ +10V) / current (0mA ~ +20mA)		▪ Input / output resolution: 12-bit ▪ Built-in RS-485 interface ▪ Differential input		

DVP-S Series Analog Module

Product Name	Description		Model Name	Certificates
Analog I/O Module	▪ 4 points of analog input voltage (-10V ~ +10V) / current (-20 mA ~ +20 mA) ▪ Input resolution: 14-bit	▪ Built-in RS-485 interface ▪ Single-ended input	DVP04AD-S	 
	▪ 4 points of analog output voltage (0V ~ +10V) / current (0 mA ~ +20 mA) ▪ Output resolution: 12-bit	▪ Built-in RS-485 interface	DVP04DA-S	
	▪ 2 points of analog output voltage (0V ~ +10V) / current (0 mA ~ +20 mA) ▪ Output resolution: 12-bit	▪ Built-in RS-485 interface	DVP02DA-S	
	▪ 6 points of analog input voltage (-10V ~ +10V) / current (-20 mA ~ +20 mA) ▪ Input resolution: 14-bit	▪ Built-in RS-485 interface	DVP06AD-S	
	▪ Analog input+output modules (6 points) ▪ 4 points of analog input voltage (-10V ~ +10V) / current (-20 mA ~ +20 mA) ▪ 2 points of analog output voltage (0V ~ +10V) / current (0 mA ~ +20 mA)	▪ Input/output resolution: 12-bit ▪ Built-in RS-485 interface ▪ Single-ended input	DVP06XA-S	

DVP-S Series Extension Module/High-Speed Module (Left-side)

Product Name	Description		Model Name	Certificates
High-Speed Analog I/O Module (Left-side)	▪ 4 groups of analog input *1 ▪ Signal range: 1~5V, 0~5V, -5~5V, 0~10V, -10~10V, 4~20mA, 0~20mA, -20~20mA ▪ Resolution: 16-bit ▪ Single channel On/Off setup enhances entire conversion efficiency ▪ Conversion time: 250µs/point ▪ Off-line alarm (1~5V, 4~20mA)	▪ Built-in RS-485 interface	DVP04AD-SL	 
	▪ 4 groups of analog output *1 ▪ Signal range: 0~10V, -10~10V, 4~20mA, 0~20mA ▪ Resolution: 16-bit ▪ Offers single channel On/Off setup ▪ Conversion time: 250µs/point			
High-Speed Load Cell Module (Left-side)	▪ 1 set of load cell module *1 ▪ Resolution: 24-bit for hardware(ADC), 32-bit for data output	▪ Connectable to 4-wire/6-wire load cell sensor ▪ Measurable range: 0~80mV/V	DVP201LC-SL	 
	▪ 1 set of load cell module *1 ▪ Resolution: 24-bit for hardware(ADC), 32-bit for data output ▪ Connectable to 4-wire/6-wire load cell sensor	▪ Measurable range: 0~80mV/V ▪ Built-in I/O control: 2DI/4DO/1AO	DVP211LC-SL	
	▪ 2 sets of load cell module *1 ▪ Resolution: 24-bit for hardware(ADC), 32-bit for data output ▪ Supports 2 channels of load cell signal input *1 ▪ Resolution: 20-bit for hardware(ADC), 16-bit for data output ▪ Connectable to 4-wire/6-wire load cell sensor ▪ Measurable range: 0~6mV/V	▪ Connectable to 4-wire/6-wire load cell sensor ▪ Measurable range: 0~80mV/V	DVP202LC-SL	
	▪ Supports 1 channel of load cell signal input *1 ▪ Resolution: 20-bit for hardware(ADC), 32-bit for data output ▪ Connectable to 4-wire/6-wire load cell sensor ▪ Measurable range: 0~6mV/V		DVP01LC-SL	
	▪ 6 points of platinum RTD (Pt100, Pt1000, Ni100, Ni1000) sensor input ▪ Resolution: 0.1°C		DVP06PT-S	
	▪ 4 points of platinum RTD (Pt100, Pt1000, Ni100, Ni1000) sensor input *1 (Version 4.06 and above supports Pt1000, Ni100, Ni1000) ▪ Resolution: 0.1°C ▪ Built-in RS-485 interface		DVP04PT-S	
Temperature Measurement Module	▪ 4 points of thermocouple (J, K, R, S, T type) sensor input *1 ▪ Resolution: 0.1°C ▪ Built-in RS-485 interface		DVP04TC-S	 
	▪ 2 points of universal analog input: 0~10V, 0~20mA, 4~20mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1°C ▪ 4 points of NPN transistor output: 24V _{DC} /300mA		DVP02TUN-S New	
	▪ 2 points of universal analog input: 0~10V, 0~20mA, 4~20mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1°C ▪ 4 points of relay output: 24V _{DC} /3A		DVP02TUR-S New	
	▪ 2 points of universal analog input: 0~10V, 0~20mA, 4~20mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1°C ▪ 2 points of analog output: 0~10V, 0~20mA, 4~20mA ▪ Output point: built-in PID program control/manual control		DVP02TUL-S New	

*1. Digital/analog photocoupler isolation. No isolation among channels.

Ordering Information

DVP-S Series Extension Module/High-Speed Module (Left-side)

Product Name	Description	Model Name	Certificates
Positioning Module	Servo position control module (single axis, 200 kHz)	DVP01PU-S	
Communication Module	DeviceNet slave communication module PROFIBUS DP slave communication module	DVPDT01-S DVPPF01-S	
Left-Side High-Speed Communication Module	Ethernet communication module, 10/100 Mbps DeviceNet master communication module, 500 Kbps CANopen master communication module, 1 Mbps PROFIBUS DP slave communication module , 12 Mbps RS-485/RS-422, serial communication module, 460 Kbps BACnet MS/TP Slave communication module, 460 Kbps	DVPEN01-SL DVPDNET-SL DVPCOPM-SL DVPPF02-SL DVPSCM12-SL DVPSCM52-SL	
Remote I/O Module	RS-485 remote I/O module, connectable to DVP-S series I/O modules Ethernet remote I/O module, connectable to DVP-S series I/O modules DeviceNet remote I/O module, connectable to DVP-S series I/O modules PROFIBUS remote I/O module, connectable to DVP-S series I/O modules	RTU-485 RTU-EN01 RTU-DNET RTU-PD01	
Remote Temperature Control Module	<ul style="list-style-type: none"> ▪ 2 points of universal analog input: 0~10V, 0~20mA, 4~20mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1°C ▪ 4 points of NPN transistor output: 24V_{dc}/300mA ▪ Output point: built-in PID program control/manual control <ul style="list-style-type: none"> ▪ 2 points of universal analog input: 0~10V, 0~20mA, 4~20mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1°C ▪ 4 points of relay output: 24V_{dc}/3A ▪ Output point: built-in PID program control/manual control <ul style="list-style-type: none"> ▪ 2 points of universal analog input: 0~10V, 0~20mA, 4~20mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1°C ▪ 2 points of analog output: 0~10V, 0~20mA, 4~20mA ▪ Output point: built-in PID program control/manual control 	DVP02TKN-S New DVP02TKR-S New DVP02TKL-S New	

Communication Converter

Product Name	Description	Model Name	Certificates
Converter	USB to RS-485 converter	IFD6500	
	USB to CAN converter	IFD6503	
	USB to RS-485 converter	IFD6530	
	MODBUS TCP to RS-232/485 converter	IFD9506	
	EtherNet/IP to RS-232/485 converter	IFD9507	
	DeviceNet to RS-232/485 converter	IFD9502	
	CANopen to RS-232/485 converter	IFD9503	
	RS-232 to RS-422/485 isolated converter	IFD8500-A	
	RS-485 to RS-422 isolated repeater	IFD8510-A	
	RS-422/485 to RS-232 addressable isolated converter	IFD8520	

DVP-PM Series

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates	
Standard Motion Controller	100~240V _{AC}	Differential	16	16	DVP10PM00M		
Advanced Motion Controller		(Built-in 4-axis of independent 1MHz pulse output)					
Advanced Motion Controller	100~240V _{AC}	Differential	8	8	DVP20PM00DT		
		(Built-in 2-axis of independent 500 kHz pulse output)			DVP20PM00D		
Extension Module		Description			Model Name		
DVP-PM communication card		Ethernet/CANopen communication card			DVP-FPMC		
Execution time of basic instructions		0.13μs		Execution time of MOV instruction		3.74 μs	

DVP-MC Series

Product Name	Power Supply	Communication Protocol	Axes Controlled	Inputs	Outputs	Model Name	Certificates
Multi-axis Motion Controller	24V _{DC}	CANopen DS402	16	8	4	DVP10MC11T	
			24	16	8	DVP15MC11T New	
			6	16	8	DVP15MC11T-06 New	
		EtherCAT	24	16	8	DVP50MC11T New	
			6	16	8	DVP50MC11T-06 New	

TP Series

Product Name	Description								Model Name	Certificates
TP02	Resolution: 160 x 32, Serial COM ports: RS-232 & RS-485								TP02G-AS1	
TP04	Resolution: 128 x 64, Serial COM ports: RS-232 & RS-422/RS-485								TP04G-AS2	
	Resolution: 192 x 64, Serial COM ports: RS-232 & RS-422/RS-485								TP04G-AL2	
	Resolution: 192 x 64, Serial COM ports: RS-232								TP04G-AL-C	
	Resolution: 192 x 64, Serial COM ports: RS-232 & RS-422/RS-485, 0 ~ 9 numeric keys available								TP04G-BL-C	
TP04P	Resolution: 192 x 64 Serial COM ports: USB & RS-485*2	4DI(60Hz)	4DO					Relay	TP04P-08TP1R	
		8DI	8DO					Relay	TP04P-16TP1R	
		16DI	16DO					Relay	TP04P-32TP1R	
		8DI	8DO	4AI	2AO			Relay	TP04P-22XA1R	
		8DI	8DO	2AI	1AO	2PT		Relay	TP04P-21EX1R	
		8DI	8DO					Transistor	TP04P-16TP1T	
		16DI	16DO					Transistor	TP04P-32TP1T	
		8DI	8DO	4AI	2AO			Transistor	TP04P-22XA1T	
		8DI	8DO	2AI	1AO	2PT		Transistor	TP04P-21EX1T	
		9DI	16DO	4AI	6AO		2AX ¹	1LC	Transistor	TP04P-20EXL1T
TP70P	Resolution: 800 x 400 Serial COM ports: USB & RS-485*2	8DI	8DO					Relay	TP70P-16TP1R	
		16DI	16DO					Relay	TP70P-32TP1R	
		8DI	8DO	4AI	2AO			Relay	TP70P-22XA1R	
		8DI	8DO	2AI	1AO	2PT		Relay	TP70P-21EX1R	
		8DI	8DO					Transistor	TP70P-16TP1T	
		16DI	16DO					Transistor	TP70P-32TP1T	
		8DI	8DO	4AI	2AO			Transistor	TP70P-22XA1T	
		8DI	8DO	2AI	1AO	2PT		Transistor	TP70P-21EX1T	
		17DI	24DO		4AO		2AX ¹	1LC	Transistor	TP70P-211LC1T
TP08	Resolution: 240 x 128, Serial COM ports: RS-232 & RS-422/RS-485, 0 ~ 9 numeric keys available								TP08G-BT2	

*1: Universal analog input (mA, V, RTD)

Software

Product Name	Description	OS (Windows based software)
ISPSoft	PLC editing software for AH, AS and DVP Series (supports 5 programming languages: LD, FBD, SFC, ST, IL)	Windows 2000, XP, Vista, Windows 7 (32-bit/64-bit)
WPLSoft	Programming software for DVP Series	Windows 98, Me, NT4.0, 2000, XP, Vista, Windows 7 (32-bit/64-bit)
TPEditor	Editing software for TP Series	Windows 98, Me, NT4.0, 2000, XP, Vista, Windows 7 (32-bit/64-bit)
PMSoft	Programming software for DVP-PM series	Windows 2000, XP, Vista, Windows 7 (32-bit/64-bit)
DCISoft	Delta communication integration software	Windows 2000, XP, Vista, Windows 7 (32-bit/64-bit)
DeviceNet Builder	DeviceNet configuration software	Windows 2000, XP, Vista, Windows 7 (32-bit/64-bit)
CANopen Builder	CANopen configuration software	Windows 2000, XP, Vista, Windows 7 (32-bit/64-bit)
NetView Builder	CAN bus message analysis software	Windows 2000, XP, Vista, Windows 7 (32-bit)

Ordering Information

Starter Kit

Product Name	Model Name	Contents
New Delta PLC Starter Kit	UT-14SS2-A	DVP14SS211R (PLC), DOP-B07S410 (HMI) and accessory
	UT-12SE-A1	DVP12SE11R (PLC), DOP-B07E411 (HMI) and accessory

Industrial Power Supply

Series	Power Supply	Inputs	Outputs	Power	Output Current	Model Name	Certificates
DVP	1-phase	85~264V _{AC}	24V _{DC}	24W	1A	DVPPS01	
				48W	2A	DVPPS02	
				120W	5A	DVPPS05	

*Note: For more ordering information, please refer to the catalogue for Delta Industrial Power Supply.

Accessories

Type	Model name	Description	Specification		Applicable Modules
			Length	Connector / Terminal block	
PLC Programming and Serial Communication Cable	UC-PRG015-01A	Communication cable for PLC (mini USB) to PC	1.5 m	PC (USB↔mini USB) PLC	DVP-SE/DVP-SX2/AH500
	UC-PRG015-02A	Communication cable for TP (USB B type) to PC	1.5 m	PC (USB↔USB B type) TP	TP70P/TP04P / DOP
	UC-PRG020-12A	Communication cable for PLC (DB9 female / 8-pin mini-DIN male) to PC	2 m	PC (DB9 female↔8-pin mini-DIN male) PLC	DVP/TP RS-232
	UC-PRG030-01A	Communication cable for PLC (mini USB) to PC	3 m	PC (USB↔mini USB) PLC	DVP-SE/SX2 AH500
	UC-PRG030-02A	Communication cable for TP (USB B type) to PC	3 m	PC (USB↔USB B type) TP	TP70P / TP04P / DOP
	UC-PRG030-10A	Communication cable for PLC / HMI / TP (DB9 female) to PC	3 m	PC (DB9 female↔DB9 female) PLC/HMI/TP	PLC/HMI/TP (DB9 female)
	UC-PRG030-20A	Communication cable for PLC / HMI (RJ45) to PC	3 m	PC (RJ45↔RJ45) PLC/HMI	DVP-SE DVPEN02-L AHCPU5□□-EN AH10EN-5A
	UC-MS010-02A	Communication cable for PLC (8-pin mini-DIN male) to PC	1 m	PC (DB9 female↔8-pin mini-DIN male) PLC	DVP PLC RS-232
	UC-MS020-01A	Communication cable for PLC (8-pin mini-DIN male) to PC	2 m	PC (DB9 female↔8-pin mini-DIN male) PLC	
	UC-MS020-06A	Communication cable for PLC (8-pin mini-DIN male) to HMI	2 m	HMI (DB9male↔8-pin mini-DIN male) PLC	
	UC-MS030-01A	Communication cable for PLC (8-pin mini-DIN male) to PC	3 m	PC (DB9 female↔8-pin mini-DIN male) PLC	
	UC-MS030-06A	Communication cable for PLC (8-pin mini-DIN male) to HMI	3 m	HMI (DB9male↔8-pin mini-DIN male) PLC	
I/O External Terminal Module	UC-ET010-24A	I/O extension cable for connecting external terminal modules	1 m	PLC (MILIDC40↔IDC40) external terminal modules	DVP32SM11N↔UB-10-ID32A DVP32SN11TN↔UB-10-OT32A
	UC-ET010-24B	I/O extension cable for connecting external terminal modules	1 m	PLC (MILIDC40↔IDC40) external terminal modules (shielded wire)	DVP32SM11N↔UB-10-ID32A DVP32SN11TN↔UB-10-OT32A
	UC-ET010-24C	I/O extension cable for connecting external terminal modules	1 m	PLC (MILIDC40↔IDC20x2) external terminal modules	DVP32SN11TN↔UB-10-OR16A
	UC-ET010-24D	I/O extension cable for connecting external terminal modules	1 m	PLC (MILIDC40↔IDC20x2) external terminal modules (shielded wire)	DVP32SN11TN↔UB-10-OR16A
	UC-ET020-24B	I/O extension cable for connecting external terminal modules	2 m	PLC (MILIDC40↔IDC40) external terminal modules (shielded wire)	DVP32SM11N↔UB-10-ID32A DVP32SN11TN↔UB-10-OT32A
	UC-ET020-24D	I/O extension cable for connecting external terminal modules	2 m	PLC (MILIDC40↔IDC20x2) external terminal modules (shielded wire)	DVP32SN11TN↔UB-10-OR16A
	UC-ET030-24B	I/O extension cable for connecting external terminal modules	3 m	PLC (MILIDC40 ↔ IDC40) external terminal modules (shielded wire)	DVP32SM11N↔UB-10-ID32A DVP32SN11TN↔UB-10-OT32A
	UC-ET030-24D	I/O extension cable for connecting external terminal modules	3 m	PLC (MILIDC40 to IDC20x2) external terminal modules (shielded wire)	DVP32SN11TN↔UB-10-OR16A

Motion Control Cable / Industrial Communication Cable	UC-CMC003-01A	CANopen communication cable	0.3m	--	DVP/CP02-H2 TAP-CN03 DVP50MC11T New DVP50MC11T-06 New
	UC-CMC005-01A	CANopen communication cable	0.5m	--	
	UC-CMC010-01A	CANopen communication cable	1m	--	
	UC-CMC015-01A	CANopen communication cable	1.5m	--	
	UC-CMC020-01A	CANopen communication cable	2m	--	
	UC-CMC030-01A	CANopen communication cable	3m	--	
	UC-CMC050-01A	CANopen communication cable	5m	--	
	UC-CMC100-01A	CANopen communication cable	10m	--	
	UC-CMC200-01A	CANopen communication cable	20m	--	
	UC-EMC003-02A	EtherCAT communication cable	0.3m	--	
	UC-EMC005-02A	EtherCAT communication cable	0.5m	--	
	UC-EMC010-02A	EtherCAT communication cable	1m	--	
	UC-EMC020-02A	EtherCAT communication cable	2m	--	
	UC-EMC050-02A	EtherCAT communication cable	5m	--	
	UC-EMC100-02A	EtherCAT communication cable	10m	--	
	UC-EMC200-02A	EtherCAT communication cable	20m	--	

Accessories

Type	Model Name	Description	Specification		Applicable Modules
			Length	Connector/Terminal Block	
Industrial Communication Cable	UC-DN01Z-01A	DeviceNet/CANopen communication cable (Trunk cable - thick)	On customer's demand (up to 305 m)	--	DeviceNet/CANopen related models
	UC-DN01Z-02A	DeviceNet/CANopen communication cable (Drop cable - thin)		--	
	UC-PF01Z-01A	PROFIBUS communication cable		--	PROFIBUS related models
External Terminal Module	UB-10-OR16A	external terminal module for DVP32SN output module	--	16-point relay output, 20-pin MIL	DVP32SN11TN
	UB-10-OT32A	external terminal module for DVP32SN output module	--	32-point transistor output, 40-pin MIL	DVP32SN11TN
	UB-10-ID32A	external terminal module for DVP32SM digital input module	--	32-point input, MIL	DVP32SM11TN
Connector	UN-03EN-04A	RJ45 connector	--	--	--
	UN-03PF-01A	PROFIBUS connector	--	--	PROFIBUS related models
	UN-03PF-02A	PROFIBUS connector	--	--	
	UN-03PF-03A	PROFIBUS connector	--	--	
Peripheral Accessory	Data backup memory card (DVP-EH3 only)				DVP-512FM
	Data backup memory card (DVP-ES2 only)				DVP-E64FM
	Data backup memory card (64k words)				DVPPCC01
	Data backup memory card (TP only)				TP-PCC01
	Communication cable for PC (9-pin & 25-pin D-Sub) and PLC, 1.5 m				DVPACAB215
	Communication cable for PC (9-pin & 25-pin D-Sub) and PLC, 3m				DVPACAB230
	4 types of RS-485 connectors				ADP485-01
	Connection cable for ADP485-01 and ASDA-A series servo				ADPCAB03A
	Connection cable for ADP485-01 and ASDA-B series servo				ADPCAB03B
	I/O extension cable for DVP-ES/EX Series, 0.3m				DVPACAB403
	Extension cable for DVP-EH series PLC and extension module, 0.7 m				DVPACAB4A07
	DeviceNet/CANopen power distribution box				TAP-CP01
	DeviceNet/CANopen distribution box, 1 for 2				TAP-CN01
	DeviceNet/CANopen distribution box, 2 for 3				TAP-CN02
	DeviceNet/CANopen distribution box, 2 for 3 RJ45				TAP-CN03
	3.6V lithium battery (unchargeable) for DVP-EH/SX Series PLC				DVPABT01
	Terminal resistance for CANopen communication (RJ45)				TAP-TR01
	Programming cable for TP Series				UCPRG030-10A

Global Operations

ASIA (Taiwan)



Taoyuan
Technology Center
(Green Building)



Taoyuan Plant 1



Taoyuan Plant
(Diamond-rated Green Building)

ASIA (China)



Wujiang Plant 3



Delta Electronics



ASIA (Japan)



Tokyo Office

ASIA (India)



Rudrapur Plant
(Green Building)

EUROPE



Amsterdam, Netherlands

AMERICA



Research Triangle Park

▲ Factories 4 ■ Branch Offices 122 ○ R&D Centers 5 □ Distributors 733





Smarter. Greener. Together.

Industrial Automation Headquarters

Delta Electronics, Inc.

Taoyuan Technology Center
No.18, Xinglong Rd., Taoyuan District,
Taoyuan City 33068, Taiwan
TEL: 886-3-362-6301 / FAX: 886-3-371-6301

Asia

Delta Electronics (Shanghai) Co., Ltd.

No.182 Minyu Rd., Pudong Shanghai, P.R.C.
Post code : 201209
TEL: 86-21-6872-3988 / FAX: 86-21-6872-3996
Customer Service: 400-820-9595

Delta Electronics (Japan), Inc.

Tokyo Office
Industrial Automation Sales Department
2-1-14 Shibadaimon, Minato-ku
Tokyo, Japan 105-0012
TEL: 81-3-5733-1155 / FAX: 81-3-5733-1255

Delta Electronics (Korea), Inc.

Seoul Office
1511, 219, Gasan Digital 1-Ro., Geumcheon-gu,
Seoul, 08501 South Korea
TEL: 82-2-515-5305 / FAX: 82-2-515-5302

Delta Energy Systems (Singapore) Pte Ltd.

4 Kaki Bukit Avenue 1, #05-04, Singapore 417939
TEL: 65-6747-5155 / FAX: 65-6744-9228

Delta Electronics (India) Pvt. Ltd.

Plot No.43, Sector 35, HSIIDC Gurgaon,
PIN 122001, Haryana, India
TEL: 91-124-4874900 / FAX : 91-124-4874945

Delta Electronics (Thailand) PCL.

909 Soi 9, Moo 4, Bangpoo Industrial Estate (E.P.Z),
Pattana 1 Rd., T.Phraksa, A.Muang,
Samutprakarn 10280, Thailand
TEL: 66-2709-2800 / FAX : 662-709-2827

Delta Energy Systems (Australia) Pty Ltd.

Unit 20-21/45 Normanby Rd., Notting Hill Vic 3168, Australia
TEL: 61-3-9543-3720

Americas

Delta Electronics (Americas) Ltd.

Raleigh Office
P.O. Box 12173, 5101 Davis Drive,
Research Triangle Park, NC 27709, U.S.A.
TEL: 1-919-767-3813 / FAX: 1-919-767-3969

Delta Greentech (Brasil) S/A

São Paulo Office
Rua Itapeva, 26 – 3° Andar - Bela Vista
CEP: 01332-000 – São Paulo – SP - Brasil
TEL: 55-11-3530-8642 / 55-11-3530-8640

Delta Electronics International Mexico S.A. de C.V.

Mexico Office
Vía Dr. Gustavo Baz No. 2160, Colonia La Loma,
54060 Tlalnepantla Estado de Mexico
TEL: 52-55-2628-3015 #3050/3052

EMEA

Delta Electronics (Netherlands) BV

Eindhoven Office
De Witbogt 20, 5652 AG Eindhoven, The Netherlands
MAIL: Sales.IA.EMEA@deltaww.com
MAIL: Sales.IA.Benelux@deltaww.com

Delta Electronics (France) S.A.

ZI du bois Chaland 2 15 rue des Pyrénées,
Lisses 91056 Evry Cedex, France
MAIL: Sales.IA.FR@deltaww.com

Delta Electronics Solutions (Spain) S.L.U

Ctra. De Villaverde a Vallecas, 265 1º Dcha Ed.
Hormigueras – P.I. de Vallecas 28031 Madrid
C/Llull, 321-329 (Edifici CINC) | 22@Barcelona, 08019 Barcelona
MAIL: Sales.IA.Iberia@deltaww.com

Delta Electronics (Italy) Srl

Ufficio di Milano Via Senigallia 18/2 20161 Milano (MI)
Piazza Grazioli 18 00186 Roma, Italy
MAIL: Sales.IA.Italy@deltaww.com

Delta Electronics (Germany) GmbH

Coesterweg 45, D-59494 Soest, Germany
MAIL: Sales.IA.DACH@deltaww.com

Delta Energy Systems LLC (CIS)

Vereyskaya Plaza II, office 112 Vereyskaya str.
17 121357 Moscow, Russia
MAIL: Sales.IA.RU@deltaww.com

Delta Greentech Elektronik San. Ltd. Sti. (Turkiye)

Serifali Mah. Hendem Cad. Kule Sok. No: 16-A
34775 Umraniye / Istanbul
MAIL: Sales.IA.Turkey@deltaww.com

Delta Energy Systems AG (Dubai BR)

P.O. Box 185668, Gate 7, 3rd Floor, Hamarain Centre,
Dubai, United Arab Emirates
MAIL: Sales.IA.MEA@deltaww.com