

Plug PowerTOP® Xtra

Part no. 13248




- screw terminals
- rubberized handle area
- frame terminals
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides

Technical specifications

| | |
|---------------------------|---|
| Ampere | 63 A |
| Poles | 5 p |
| Voltage | 50-500 V |
| Clock position | 1 h |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier, nickel plated contacts |
| Protection type | IP 67 |
| Weight | 882 g |
| Declaration of Conformity | DE, VDE, CN, CQC |

Drawing



| Drawing 2 MB 225 | Amp. Poles | 63 | | | 125 | | |
|--------------------------------------|---------------|-----|-----|-----|-----|-----|-----|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 250 | 250 | 250 | 290 | 290 | 290 |
| | b | 114 | 114 | 114 | 130 | 130 | 130 |
| | y | 36 | 36 | 36 | 49 | 49 | 49 |
| Terminal for cond. cross | | 6 | 6 | 6 | 25 | 25 | 25 |
| section (mm ²) min.-max. | | -16 | -16 | -16 | -50 | -50 | -50 |

Stecker PowerTOP® Xtra

Bestellnr. 13248




- Schraubkontakt
- gummierte Griffflächen
- Rahmenklemmen
- hochwärmebeständige Kontaktträger
- vernickelte Kontakte
- Verschraubung mit Abdichtung
- Zugentlastung und Kabelknickschutz
- Gehäuse mit Gewindeverschluss
- Sicherungsschieber für Gehäuse und Verschraubung

Technische Daten

| | |
|-------------------|---|
| Ampere | 63 A |
| Pole | 5 p |
| Volt | 50-500 V |
| Uhrzeitstellung | 1 h |
| Anschlussstechnik | Schraubkontakt |
| Kontakt | hochwärmebeständige Kontaktträger, vernickelte Kontakte |
| Schutzart | IP 67 |
| Gewicht | 882 g |
| Prüfzeichen | DE, VDE, CN, CQC |

Abmessungen



| Zeichnung 2 MB 225 | Amp. Pole | 63 | | | 125 | | |
|-------------------------|--------------|-----|-----|-----|-----|-----|-----|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Maße in mm | a | 250 | 250 | 250 | 290 | 290 | 290 |
| | b | 114 | 114 | 114 | 130 | 130 | 130 |
| | y | 36 | 36 | 36 | 49 | 49 | 49 |
| Klemmen für Leiterquer- | | 6 | 6 | 6 | 25 | 25 | 25 |
| schnitt von bis mm? | | -16 | -16 | -16 | -50 | -50 | -50 |



Plug PowerTOP® Xtra - 13248

2007511IN
Rev. 0 / 2020-02-14

Release Page:

Document title:

Plug PowerTOP® Xtra - 13248
Stecker PowerTOP® Xtra - 13248

Document number: 2007511IN

Revision: 0

Language: IN

Department: Engineering/ELE

Reviewer/Date:

Gottwald Florian:
2020-02-14

**Classification
(Confidentiality):** Nordex Internal
Purpose

Status: Released

Approver/Date:

Paashaus Steven:
2020-02-14

Main AST: 21845

**External document
number:** Stecker PowerTOP®
Xtra - 13248

External Version:

**External Release
Date:** 13.02.2020

Source: SUPPLIER

This release page refers to the document Plug PowerTOP® Xtra - 13248, Rev. 0/2020-02-14 with 2 pages.
Document has been electronically created and released.